

Data Sheet

Screwless Pluggable Terminal Block (Plug)

Pitch: 2,54 mm


Serie: A26061

Customer Information for special Item

EDCON Customer : xxxxxx

Customer Version No. : xx

EDCON-COMPONENTS



Technical Description

Electrical:

	UL/UR	CE	VDE
Rated voltage:	150V	160V	
Rated current:	3A	3A	
Withstanding Voltage: AC/1min:	2000V	2000V	
Operating Temperature:	-60°C ~ +105°C		

Mechanical:

Strip length: mm	5 ~ 6	5 ~ 6	
Wire range: Solid wire: AWG	24-20	0,5mm ²	
Wire range: Stranded wire:AWG	24-20	0,5mm ²	

Material:

Housing Terminal Body:	PPA-GF UL94V-0
Material Screw:	Stainless steel
Material Terminal:	Copper Matte Tin plated over Nickel

Drawing (Dimension in mm)

No Drawing in
the moment
available

Item No.

- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8
- 9


Tolerances unless otherwise specified (mm)				
X	X.X	X.XX	X.XXX	Angle
±	±	±	±	±3°
DRW:	Jason	CHKD	Wilson	MATL:
APPD:	Schumi			FINISH
			Jamy	TOLERANCE
				Mason
				DATE
				22.11.2019
				Sheet No.
				1 from 3

**Screwless Pluggable
Terminal Block (Plug)**

Part No.: **A26061**

Customer:

EDCON-COMPONENTS



Ordering Informations

Serie	No. of Pos.	Body Color	Screw Function	Approval Code	ROHS	Packing	EDCON Cust. No.	Customer Version		
A26061	04	BK	C	N	R	B	xxxxxx	xx		

Pitch
2,54

XX= Number of Pos.		C= Screwless Type	N= NON Approval	R= ROHS Conform	B= Bulk-Ware	xxxxxx= Customer Number	xx= Customer Version ??(Printing)
Standard 2x2 ~ 2x16Pos.			1= UL-Approval for Material	N= NON ROHS Conform	I= Individual Package		
			A= UL /UR Approval Please consult EDCON for available				
			B= VDE Approval Please consult EDCON for available				
	BK= Black		C= TÜV Approval Please consult EDCON for available				

Screwless Pluggable Terminal Block (Plug)	
Part No.:	A26061
Customer:	

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	22.11.2019
APPD:	Schumi			FINISH	Jamy		Sheet No.		3 from 3