



Technical Specification


Features

- Closed magnetic circuit structure allows high density mounting on a pcb board, mounting while preventing crosswalk.
- Extremely high reliability due to entirely monolithic construction.
- Low DC resistance structure of electronic to prevent wasteful electric power consumption.
- High current application rating look at range.

Applications

Power lines

Dimensions




Chip Dimensions

L (mm)	W (mm)	T (mm)	RW (mm)
0,60 +/-0,03	0,3 +/-0,03	0,3 +/-0,03	0,15 +/-0,05

Test conditions

Specifications	Test Conditions		Value	Unit	Tol.
Impedance	100Mhz	Z	22	Ω	+/- 25%
Max. Impedance		Z		Ω	typ.
DC-Resistance		R _{DC}	0,065	Ω	max.
Rated Current		I _{DC}	900	mA	max.

Typical Impedance v.s. Frequency Curve:



Circuit



Ferrit Chip Bead Size 0201

Serie No.: **G12018**
 Customer:

DRW:	Johnny	CHKD	Carlo	MATL:	Wor	DATE	12.01.2013
APPD:	Elva			FINISH	Vienna	Sheet	1 from 2



P.C.B. Layout Dimension

	(mm)
A	0,20 ~ 0,36
B	0,61 ~ 1,02
C	0,33 ~ 0,41




Soldering Profile

Soldering Profile for Lead Soldering



Soldering Profile for Lead Free Soldering



Ordering Information

Serie	Impedance	Tolerance	Current	ROHS	Packing
G12018	220	N	901	R	TR

220= 22 Ohm	N= Tolerance 25%	901= 0,90A	R= ROHS conform	BU= Bulk Ware TR= Tape/Reel
			N=NON ROHS conform	

Ferrit Chip Bead Size 0201

Serie No.:	G12018
Customer:	

DRW:	Johnny	CHKD	Carlo	MATL:	Wor	DATE	12.01.2013
APPD:	Elva			FINISH	Vienna	Sheet	2 from 2