



**Technical Specification**

**Features**

- Closed magnetic circuit structure allows high density mounting on a PCB board, mounting while preventing crosswalk.
- Extremely high reliability due to entirely monolithic construction.
- Low DC resistance structure of electronic to prevent wasteful electric power consumption.
- High current application rating look at range.

**Dimensions**



Chip Dimensions		Size Code	
		0402	1005
L (mm)	W (mm)	T (mm)	RW (mm)
1,0±0,15	0,5±0,15	0,5±0,15	0,25±0,1

**Specifications / Test conditions**

	Min	Typ.	Max	Unit	Order Code
Impedance: ( Z )		<b>70</b>		<b>Ω</b>	<b>700</b>
DC-Resistance: (RDC)	--	<b>0,30</b>	--	<b>Ω</b>	
Rated Current: ( IDC )	--	<b>200</b>	--	<b>mA</b>	<b>201U</b>
Operating Temperature: ( °C )	<b>-.55°C ~ +125°C</b>				
Tolerance: ( % )	<b>25</b>	Tolerance Code:		<b>N</b>	
Test-Conditions: ( MHz)	<b>100</b>	Material Code:		<b>U</b>	

**Typical Impedance v.s. Frequency Curve:**

**Circuit**



IMPEDANCE ( Ohm)

In the moment not available

FREQUENCY (Mhz)

**For General Lines Chip Beads**

Serie No.: **G12023-700-201U**

Customer:

DRW:	Johnny	CHKD	Carlo		Wor	DATE	19.02.2023
APPD:	Elva				Vienna	Sheet	1 from 2

Copyright by EDCON S.Tiede



**Soldering Profile for Lead Soldering**

**Soldering Profile for Lead Free Soldering**



**Ordering Information**

Serie	Tolerance	Special	ROHS	Packing
-------	-----------	---------	------	---------

G12023-700-201U	N	X	R	TR
-----------------	---	---	---	----

N= Tolerance 25%	X= No special function	R= ROHS conform	BU= Bulk Ware
		N=NON ROHS conform	

For General Lines Chip Beads	
Serie No.:	G12023-700-201U
Customer:	

DRW:	Johnny	CHKD	Carlo	Wor	DATE	19.02.2023
APPD:	Elva			Vienna	Sheet	2 from 2

Copyright by EDCON S.Tiede