




Technical Specification

Features

- Closed magnetic circuit structure allows high density mounting on a PCB board, mounting while preventing crosswalk.
- Extremely high reliability due to entirely monolithic construction.
- Low DC resistance structure of electronic to prevent wasteful electric power consumption.
- High current application rating look at range.

Dimensions




| Chip Dimensions | | Size Code | Size Dimension |
|-----------------|----------|-----------|----------------|
| | | 0201 | 0603 |
| L (mm) | W (mm) | T (mm) | RW (mm) |
| 0,6±0,05 | 0,3±0,05 | 0,3±0,05 | 0,15±0,05 |

Specifications / Test conditions

| | Min | Typ. | Max | Unit | Order Code |
|-------------------------------|----------------|-----------------|-----|------|------------|
| Impedance: (Z) | | 60 | | Ω | 600 |
| DC-Resistance: (RDC) | -- | 0,30 | -- | Ω | |
| Rated Current: (IDC) | -- | 200 | -- | mA | 201 |
| Operating Temperature: (°C) | -55°C ~ +125°C | | | | |
| Tolerance: (%) | 25 | Tolerance Code: | | N | |
| Test-Conditions: (MHz) | 100 | Material Code: | | D | |

Typical Impedance v.s. Frequency Curve:

Circuit



IMPEDANCE (Ohm)

In the moment not available

FREQUENCY (Mhz)

For General Lines Lower DCR Chip Beads

Serie No.: **G12035-600-201**

Customer:


| | | | | | | | |
|-------|--------|------|-------|--|--------|-------|------------|
| DRW: | Johnny | CHKD | Carlo | | Wor | DATE | 19.02.2023 |
| APPD: | Elva | | | | Vienna | Sheet | 1 from 2 |

Copyright by EDCON S.Tiede



Soldering Profile for Lead Soldering

Soldering Profile for Lead Free Soldering



Ordering Information

| Serie | Tolerance | Special | ROHS | Packing |
|-------|-----------|---------|------|---------|
|-------|-----------|---------|------|---------|

| | | | | |
|----------------|---|---|---|----|
| G12035-600-201 | N | X | R | TR |
|----------------|---|---|---|----|

| | | | |
|------------------|------------------------|--------------------|---------------|
| N= Tolerance 25% | X= No special function | R= ROHS conform | BU= Bulk Ware |
| | | N=NON ROHS conform | |

For General Lines Lower DCR Chip Beads

Serie No.: **G12035-600-201**

Customer:

| | | | | | | |
|-------|--------|------|-------|--------|-------|------------|
| DRW: | Johnny | CHKD | Carlo | Wor | DATE | 19.02.2023 |
| APPD: | Elva | | | Vienna | Sheet | 2 from 2 |

Copyright by EDCON S.Tiede