

	appellation	measured value	test condition
1	Operating temperature	25/70/21	
2	Rated voltage	450VAC	
3	Rated current	1.7A	
4	Life expectancy	Class B	
5	Rated frequency	50/60Hz	
6	Rated capacitance	12 μ F	
7	Capacity deviation	$\pm 5\%$	
8	filler	Epoxy Resin	
9	Class of safety protection	P0	
10	Shell material	Plastic Shell	
11	Tangent of loss angle	≤ 0.003	100Hz
12	Derivative fashion	2-2-250 #	
13	overall size	CBB60 \varnothing D x H (\varnothing 40x72.5mm)	
14	Installation	NONE	
15	Voltage test	Between terminals	788VAC 2S No permanent Breakdown and Flash Burn
		Between terminals and case	2000VAC 2S No permanent Breakdown and Flash Burn
16	The implementation of standards	UL810	
17	certification	UL	

The request of packaging, appearance and testing

1. Packaging

- ① The product model, specification, quantity, the date of leaving factory and the production title should be marked on the inner packaging. The certificate of eligibility should be put in the packaing box.
- ② When the goods are sent to the client, the seal of packaging should be all right. The packaging should be never disrepair.

2. Appearance

- ① All product should be marked with sign, the product model, specification and the date of production.
- ② The appearance should be neatness.

3. Testing

- ① All product shoule be inspected their electric performance, while manufacturing.
- ② Before the product leaving the factory, according to the national industry standard, sample product shoule be tested with the process record.

Revision Record:

Item	Matter	Reason	Responsibility	Advantage

Product-Picture: CBB60

