



EDCON-COMPONENTS



SPECIFICATION:

Current Rating: 2 Ampere / 250VAC
 Insulator Resistance: 5000 Megaohm min.
 Dielectric Withstanding: AC 1000V
 Operating Temperature: -40°C to +85°C
 Contact Material: Copper, Alloy
 Insulator Material: Polyester, UL 94V-0
 Standard: P.B.T.
 Contact Plating: Tin,

Drawing



Door-Switch

Part No.: **Q54001**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	31.07.2026
APPD:	Schumi			FINISH	Jamy		Sheet No.		1 from 2

Customer:

www.edcon-components.com

email: info@edcon-components.com

Copyright by S.Tiede

EDCON-COMPONENTS



Ordering Informations

Serie	Body Colour	Fill with 0	Fill with 0	Fill with 0	Fill with 0	Fill with 0	ROHS	Packing		
Q54001	BK	X	X	X	X	X	R	BU		

BK= Black						N= non ROHS	BU= Bulk Ware
LG= Light Gray						R= ROHS conform	TY= Tray Packing
							TR102 = Tape/Reel Packing 1000PCS

Female Header / Single Row / Pitch 2,00mm
Part No.: Q54001
Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	31.07.2026
APPD:	Schumi			FINISH	Jamy		Sheet No.	2 from 2	

www.edcon-components.com

email: info@edcon-components.com