

EDCON-COMPONENTS



SPECIFICATION:

Current Rating:	1 Ampere / 250VAC
Insulator Resistance:	5000 Megaohm min.
Dielectric Withstanding:	AC 1000V
Operating Temperature:	.-40°C to +85°C
Contact Material:	Copper, Alloy
Insulator Material:	Polyester, UL 94V-0
Standard:	P.B.T.
Contact Plating:	Tin,

Drawing



Door-Switch

Part No.: **Q54002**

Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	31.07.2026
APPD:	Schumi			FINISH	Jamy		Sheet No.	1 from 2	

www.edcon-components.com

email: info@edcon-components.com

Copyright by S.Tiede

EDCON-COMPONENTS



Ordering Informations

Serie	Body Colour	Fill with 0	Fill with 0	Fill with 0	Fill with 0	Fill with 0	ROHS	Packing		
Q54002	BK	X	X	X	X	X	R	BU		

BK= Black						N= non ROHS	BU= Bulk Ware
LG= Light Gray						R= ROHS conform	TY= Tray Packing
							TR102 = Tape/Reel Packing 1000PCS

Female Header / Single Row / Pitch 2,00mm
Part No.: Q54002
Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	31.07.2026
APPD:	Schumi			FINISH	Jamy		Sheet No.	2 from 2	

www.edcon-components.com

email: info@edcon-components.com