



DATA SHEET

Double USB-Charger for Cars Input=12/24V

Serie: T65297

Double USB-Charger for Cars Input=12/24V	
Serie No.:	T65297
Customer:	

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	17.04.2018
APPD:	Schumi			FINISH	Jamy		Sheet No.		1 from 13



Technical Dimensions

Panel-Mount Double USB Charge Connecting
 2x 5V /2,1A Totally 4,2A/5V
 Input-Voltage DC12/24V
 Hole Dimension: 29mm
 Depth of Housing w/o Connecting Contacts= 34mm
 Depth of Housing with Connecting Contacts= 45mm
 Connecting Terminals 6,3mm TAB-Terminal
 with Protection Cap



Tolerances unless otherwise specified (mm)									
X	X.X	X.XX	X.XXX	Angle					
±	±	±	±	±3°					
DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	17.04.2018
APPD:	Schumi			FINISH	Jamy			Sheet No.	2 from 13

Double USB-Charger for Cars Input=12/24V

Part No.: **T65297**

Customer:



Double USB-Charger for Cars Input=12/24V	
Part No.:	T65297
Customer:	

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	17.04.2018
APPD:	Schumi			FINISH	Jamy		Sheet No.		3 from 13



A= 6,3x0,8mm TAB Terminal Length of Terminal 11mm

Double USB-Charger for Cars Input=12/24V	
Part No.:	T65297
Customer:	

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	17.04.2018
APPD:	Schumi			FINISH	Jamy		Sheet No.		4 from 13

www.edcon-components.com

email: info@edcon-components.com



Ordering Informations

Serie	Connecting	Special function	Special function	Special function	ROHS	Packing Code	
T65297	A	N	N	N	R	BU	
	A= 6,3mm ab-Terminal	N= No function	N= No function	N= No function	R= ROHS Conform	BU= Bulk Ware	
	X= others on request (cable)				N= NON ROHS Conform		

Double USB-Charger for Cars Input=12/24V	
Part No.:	T65297
Customer:	

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	17.04.2018
APPD:	Schumi			FINISH	Jamy		Sheet No.		12 from 13