

EDCON-COMPONENTS



Specifications

Features

Contact Positions: 09, 15, 25, 37
 Available in plug , right angle styles
 Provides ground continuity from cable to PC-board
 Available of 3 type of body dimensions measures from thre front face of mounting flange to first row of contacts.
 Various options of fasten types

Materials

Contact Brass
 Housing: PBT +30% Glass Fiber (UL 94V-0)
 Shell: cold roller steel

Electrical Characteristics

Current Rating: 5Ampere
 Withstanding Voltage: AC 1250V r.m.s.
 Insulation Resistance: 5000 Megaohms Minimum at DC500V
 Contact Resistance: 15 Milliohm Maximum
 Operation Temperature: -55°C ~ +105°C
 Applicable: P.C. Board thickness: (1,6mm)

Mechanical Characteristics:

Contact Resistance Force: 341gr. Maximum
 Contact Separation Force: 20gr. Minimum

Finishes:

Contact Plating (look Order Code)
 Shell Plating (look order code)

Dimensions (mm)

Male Contact

Pos.	9	15	25	37	50
Dim.A	30,80	39,20	53,05	69,40	66,90
Dim.B	25,00	33,30	47,05	63,50	61,10
Dim.C	16,90	25,25	38,95	55,40	52,40

Female Contact

Pos.	9	15	25	37	50
Dim.A	30,80	39,20	53,05	69,40	66,90
Dim.B	25,00	33,30	47,05	63,50	61,10
Dim.C	16,30	24,60	38,35	54,80	52,80

P.C.B. Layout

D-Sub Connector for Right angle Waterproof

Part No.: **T84003**

Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	01.09.2015
APPD:	Schumi			FINISH	Jamy		Sheet No.		1 from 4

www.edcon-components.com


email: info@edcon-components.com

EDCON-COMPONENTS



Female Contact

Male Contact



D-Sub Connector for Right angle Waterproof

Part No.: **T84003**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	01.09.2015
APPD:	Schumi			FINISH	Jamy		Sheet No.		2 from 4

Customer:

www.edcon-components.com

email: info@edcon-components.com

EDCON-COMPONENTS



Ordering Informations

Serie	No. of contacts.	Contact Type	Shell Finish	Mounting Options	No function	No function	Contact Plating	Plastic Color	ROHS	Packing
T84003	09	F	Z	D	0	0	GF	WH	R	TY

09= Contacts	F= Female	Z= chromatic					GF= Gold Flash	WH= White	R= ROHS Conform	TY= Tray Packing
09, 15, 25, 37 Contacts	M= Male	T= Tin					GA= 10µ Gold	BK= Black	N= NON ROHS Conform	BU= Bulk-Ware
		N= Nickel					GB= 15µ Gold	BL= Blue		
							GC= 30µ Gold	GY= Gray		
							GD= 50µ Gold			
			D= Rived Nuts UNC 4-40 on Front Side				SF= Selective Gold flash			
							SA= 5µ Selective Gold flash			
							SB= 10µ Selective Gold flash			
							SC= 15µ Selective Gold flash	SD= 30µ Selective Gold flash		


D-Sub Connector for Right angle Waterproof
Part No.: **T84003**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	01.09.2015	Customer:
APPD:	Schumi			FINISH	Jamy			Sheet No.	3 from 4	



Soldering Profile Curve

Classification Reflow Profile (JEDEC J-STD-020C)



D-Sub Connector for Right angle Waterproof

Part No.: **T84003**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	01.09.2015	Customer:
APPD:	Schumi			FINISH	Jamy		Sheet No.	4 from 4		