

# EDCON-COMPONENTS



## Technical Discription

Cable Wire: Standard USB-Wire  
 No of Wires: 4  
 Cable Type: Without Shielded **S0**  
 Single Shielded Order Code **S1**  
 Double Shielded Order Code **S2**  
 Temperature Range: LOK order Code TABLE  
 Material: PVC  
 Cable Type: 2464-26WX4C  
 Wire Size: 7x0,12 \* 4

Side One Connector Type USB-A

Side Two OPEN-END



Order Code	Description of Order Code
<b>A1</b>	10mm open-end and 3mm tinned ends.
<b>A2</b>	30mm open-end and 5mm tinned ends. Shield also 5mm tinned end

<b>USB-Cable Bundled</b>	
Part No.:	<b>TA20018</b>
Customer:	

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	12.04.2019
APPD:	Schumi			FINISH	Jamy		Sheet No.	1 from 2	

# EDCON-COMPONENTS



## Ordering Informations

Serie	Length of Cable (mm)	Colour of Cable	Cable Wire Type	Connector Colour	Side two OPEN-END Condit	Wire Cable Type	ROHS	Packing	Temperature Range
TA20018	xxxx	BK	A1	B	Ax	Sx	R	BU	X

2000 = mm Total Length	BK = Black	A1 = 28+28 AWG	B = Black	Ax = look Description Page 1	S0 = unshielded Round Cable	R = ROHS - conform	BU = Bundle	A = Operating Temp. Range - 45°C to +85°C
	WH = White	A2 = 26+28 AWG	W = White		S1 = Single shielded Round Cable	N = NON ROHS conform	Ix = Individual Package	
		A3 = 24+28 AWG			S2 = Double shielded Round Cable			B = Operating Temp. Range - 30°C to +70°C

**USB-Cable Bundled**

Part No.: **TA20018**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	12.04.2019	Customer:
APPD:	Schumi			FINISH	Jamy		Sheet No.		2 from 2	