



# DATA SHEET

## Precision Metal Film Resistor N-Size 5,5x16mm 2,0Watt

### Serie: X34016

**Precision Metal Film Resistor N-  
Size 5,5x16mm 2,0Watt**

Serie No.: **X34016**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	06.10.2011
APPD:	Schumi			FINISH	Jamy		Sheet No.	1 from 6	

Customer:

# EDCON-COMPONENTS



## Specifications

Temperature coefficient	Within the maximum temperature coefficient specified
Short time overload	. $\pm$ (0,5% + 0,05 $\Omega$ ) Max, with no evidence of mechanical damage.
Insulation resistance	Min. 10.000 Mega Ohm
Dielectric withstanding voltage	No evidence of flashover , mechanical damage, arcing or insulation breackdown.
Pulse overload	. $\pm$ (1,0% + 0,05 $\Omega$ ) Max., with no evidence of mechanical damage.
Terminal strength	No evidence of mechanical damage.
Resistance to soldering heat	. $\pm$ (1,0% + 0,05 $\Omega$ ) Max, with no evidence of mechanical damage.
Solderability	Min. 95% coverage.
Resistance to solvent	No deterioration of protective coating and markings.
Temperature cycling	. $\pm$ (1,0% + 0,05 $\Omega$ ) Max, with no evidence of mechanical damage.
Humidity (steady state)	. $\pm$ (2,0% + 0,05 $\Omega$ ) Max, with no evidence of mechanical damage.
Load life in humidity	Normal Type: $\pm$ (1,5% + 0,05 $\Omega$ ) Max. Non Flame Type: $\pm$ (5,0% + 0,05 $\Omega$ ) Max.
Load life	Normal Type: $\pm$ (1,5% + 0,05 $\Omega$ ) Max. Non Flame Type: $\pm$ (5,0% + 0,05 $\Omega$ ) Max.

## Features


- EIA standard color coding
- NON-Flame & NON-inductive available
- Low noise & voltage coefficient
- Low temperature coefficient range
- Wide precision range in small package
- Too low or too high ohmic value can be supplied on a case to case basis
- Nichrome resistor element provides stable performance in various environment
- Multipole epoxy coating on vacuum deposited metal film provides superior moisture protection

**Precision Metal Film Resistor N-  
Size 5,5x16mm 2,0Watt**

Part No.: **X34016**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	06.10.2011	Customer:
APPD:	Schumi			FINISH	Jamy		Sheet No.	2 from 6		

# EDCON-COMPONENTS



## Dimensions



Power Rating at 70°C	Dimension (mm)				
	D max.	L max.	d±0.05	H±3	Packing Qty
2,0W	5,5	16,0	0,7	28	5000PCS

Maximum Working Voltage	Maxi,u, Overload Voltage	Dielectric Withstanding Voltage	Tolerance	Resistange Range	T.C.R.	Special Order		
						Tolerance	Resistance Range	T.C.R.
500V	1000V	1000V	± 1%	51,1Ω ~ 1MΩ	± 50PPM/°C	± 0,10%	100Ω ~ 330KΩ	± 15PPM/°C
			± 2%	51,Ω ~ 1MΩ	± 100PPM/°C	± 0,25%	51,1Ω ~ 511KΩ	± 25PPM/°C
			± 5%	1Ω ~ 1MΩ	± 200PPM/°C	± 0,50%	51,Ω ~ 1,0MΩ	± 50PPM/°C

**Precision Metal Film Resistor N-  
Size 5,5x16mm 2,0Watt**


Part No.: **X34016**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	06.10.2011	Customer:
APPD:	Schumi			FINISH	Jamy		Sheet No.	3 from 6		


# EDCON-COMPONENTS




## Current Noise Level Curves



## Derating Curve



## Load Life



**Precision Metal Film Resistor N-  
Size 5,5x16mm 2,0Watt**

Part No.: **X34016**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	06.10.2011
APPD:	Schumi			FINISH	Jamy		Sheet No.	4 from 6	Customer:

# EDCON-COMPONENTS



## Ordering Informations

Serie	Range	Tolerance	PPM requirement	Feature	Special function	ROHS	Packing Code
-------	-------	-----------	-----------------	---------	------------------	------	--------------

<b>X34016</b>	<b>1001</b>	<b>F</b>	<b>050</b>	<b>F</b>	<b>00</b>	<b>R</b>	<b>TA</b>
---------------	-------------	----------	------------	----------	-----------	----------	-----------


<b>1001= 1KΩ</b>	<b>F= 1%</b>	<b>015= 15ppm</b>	<b>S= Standard</b>	<b>00= no function</b>	<b>R= ROHS Conform</b>	<b>BU= Bulk Ware</b>
<b>1R00= 1,0Ω</b>	<b>G= 2%</b>	<b>025= 25ppm</b>	<b>F= Non Flammability</b>			
<b>10R0= 10Ω</b>	<b>J= 5%</b>	<b>050= 50ppm</b>	<b>I= Non Inductive</b>	<b>TR= Tape Reel</b>		
<b>1000= 100Ω</b>	<b>B= 0,1%</b>	<b>100= 100ppm</b>				
Range from 1Ω ~ 1MΩ Row E96	<b>C= 0,25%</b>	<b>200= 200ppm</b>				
	<b>D= 0,5%</b>					

**Precision Metal Film Resistor N-  
Size 5,5x16mm 2,0Watt**

Part No.: **X34016**

Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	06.10.2011
APPD:	Schumi			FINISH	Jamy		Sheet No.	5 from 6	



Soldering Profile Curve

Classification Reflow Profile (JEDEC J-STD-020C)



<b>Precision Metal Film Resistor N- Size 5,5x16mm 2,0Watt</b>	
Part No.:	<b>X34016</b>
Customer:	

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	06.10.2011
APPD:	Schumi			FINISH	Jamy		Sheet No.	6 from 6	