



DATA SHEET

Wire Wound Resistor Small-Size 8,5x53mm 10Watt

Serie: X39016

**Wire Wound Resistor Small-Size
8,5x53mm 10Watt**

Serie No.: **X39016**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	21.10.2011
APPD:	Schumi			FINISH	Jamy		Sheet No.	1 from 6	

Customer:

EDCON-COMPONENTS



Specifications

Temperature coefficient	<20Ω: ±400PPM/°C; ≥20Ω: ±300PPM/°C
Short time overload	. ± (2,0% + 0,05Ω) Max, with no evidence of mechanical damage.
Dielectric withstanding voltage	No evidence of flashover , mechanical damage, arcing or insulation breackdown.
Pulse overload	. ± (5,0% + 0,05Ω) Max., with no evidence of mechanical damage.
Terminal strength	No evidence of mechanical damage.
Resistance to soldering heat	. ± (1,0% + 0,05Ω) Max, with no evidence of mechanical damage.
Solderability	Min. 95% coverage.
Resistance to solvent	No deterioration of protective coating and markings.
Temperature cycling	. ± (2,0% + 0,05Ω) Max, with no evidence of mechanical damage.
Load life in humidity	. ± (5,0% + 0,05Ω) Max, with no evidence of mechanical damage.
Load life	. ± (5,0% + 0,05Ω) Max, with no evidence of mechanical damage.
Non-flame	No evidence of flammng or cracing

Features

- Color Coating are Green
- Non-inductive type available
- Excellent flame resistance
- Too low or too high ohmic value can be supplied on a case to case basis
- Special Fusing Wire-wound resistor can be supplied on a case to case basis
- Standard 2%, 5% 10% delivery by row E24
- Tolerance 1% delivery byn row E96

**Wire Wound Resistor Small-Size
8,5x53mm 10Watt**

Part No.: **X39016**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	21.10.2011	Customer:
APPD:	Schumi			FINISH	Jamy		Sheet No.	2 from 6		

EDCON-COMPONENTS



Dimensions



Power Rating at 70°C	Dimension (mm)				
	D max.	L max.	d±0.05	H±3	Packing Qty
10W	8,5	53,0	0,75	38	1600PCS

Maximum Working Voltage	Maxi,u, Overload Voltage	Dielectric Withstanding Voltage	Tolerance	Resistange Range
500V	1000V	1/2W, 1W-S: 350V >1W-S: 5090V	± 1%	1Ω ~ 1,5KΩ
			± 2%	1Ω ~ 1,5KΩ
			± 5%	1Ω ~ 1,5KΩ

**Wire Wound Resistor Small-Size
8,5x53mm 10Watt**

Part No.: **X39016**


DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	21.10.2011
APPD:	Schumi			FINISH	Jamy		Sheet No.		3 from 6

Customer:


EDCON-COMPONENTS



Derating Curve



Heat Rise Chart



**Wire Wound Resistor Small-Size
8,5x53mm 10Watt**

Part No.: **X39016**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	21.10.2011
APPD:	Schumi			FINISH	Jamy		Sheet No.	4 from 6	Customer:

www.edcon-components.com

email: info@edcon-components.com

EDCON-COMPONENTS



Ordering Informations

Serie	Range	Tolerance	Feature	Special function	ROHS	Packing Code
-------	-------	-----------	---------	------------------	------	--------------

X39016	152	J	S	00	R	TA
---------------	------------	----------	----------	-----------	----------	-----------

152 = 1,5Ω for Tol. 5%	F = 1%	S = Standard	00 = no function	R = ROHS Conform	BU = Bulk Ware
1501 = 1,5KΩ for Tol. 1%	G = 2%	I = Non Inductive		N = NON ROHS Conform	TA = Tape Ammo Pack
	J = 5% (Standard)				TR = Tape Reel

**Wire Wound Resistor Small-Size
8,5x53mm 10Watt**

Part No.: **X39016**


DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	21.10.2011
APPD:	Schumi			FINISH	Jamy		Sheet No.		5 from 6

Customer:



Soldering Profile Curve

Classification Reflow Profile (JEDEC J-STD-020C)



Wire Wound Resistor Small-Size	
8,5x53mm 10Watt	
Part No.:	X39016
Customer:	

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	21.10.2011
APPD:	Schumi			FINISH	Jamy		Sheet No.	6 from 6	