THT, Radial E-Cap., Ultra Low Impedance Enabled high ripple current by a reduction of impedance at high frequency. high reliability withstading to 5000hrs load life at 105°C, Long Lead, ROHS Conform, Packing Bulk-Ware into Polybag

Items	Performance Characteristics
Operating temperature range	.-40°C +105°C
Leakage currrent max.	I = 0,01CV + 3µA whichever is greater (after 2 minutes) I = 0,03CV + 4µA whichever is greater (after 1 minutes)
Capacitance tolerance	±20% at 120Hz, 20°C
Dissipation factor max. (at 120Hz, 20°C)	Capacitance > 1000µF ; tanQ increases by 0,02 for each 1000µF from below value.

WV	6,3	10	16	25	35	50	63	100
TanQ	0,22	0,19	0,16	0,14	0,12	0,10	0,09	0,08

Low temperature characteristics (Impedance ratio at 120Jz)	Z-40°C / Z+20°C	Z-25°C / Z+20°C
	3	2

Load life (after application of the rated voltage for 5000hrs at 105°C)		
	Leckage Current	Less than specified Value
	Capacitance Change	Within ±25% off initial Value
	TanQ	Less than 200% of specified value
	Ø5 , Ø6,3 : 2000hours; Ø8: 3000hours : Ø10 : 5000hours	
Shelf life (at 105°C)	After 1000 hours no load test, leackage current, capacitance and tanQ are same as load life value.	

FREQUENY COEFFICIENT OF PERMISSIBLE RIPPE CURRENT

µF	Frequency	120Hz	1kHz	10kHz	50kHz	100kHz≤
~33		0,42	0,70	0,90	0,95	1,00
47~270		0,50	0,73	0,92	0,96	1,00
330~680		0,55	0,77	0,94	0,97	1,00
1000~1500		0,60	0,80	0,96	0,98	1,00
2000~		0,70	0,85	0,98	0,99	1,00

Technical Details

Range (µF)	100	ØD(mm)	6,3
Voltage	25	L(mm)	11,0
Impedance (Ω)	0,15	F(mm)	2,5
Ripple Current (mA)	405	Ød(mm)	0,5
ESR (Ω) max.at 20°C 10KHz	-.-	α(mm)	1,5
Lifetime (hrs)	2000	-.-	-.-
Operating- Temperature Range (°C)	.-40°C ~ +105°C	-.-	-.-



ØD	5	6,3	8	10	12,5	16	18	22
F	2	2,5	3,5	5,0	5,0	7,5	7,5	10,0
Ød	0,5			0,6		0,8		
α	1,5			2.0				3,0

DRW:	Lexua	CHKD	Wilson	MATL:	ChuChu	DATE	23.12.2024
APPD:	Jimmy			FINISH	Josy	Sheet	1 from 2

Copyright by S.Tiede

EDCON COMPONENTS
A MEMBER OF EDCON-GROUP

THT, Radial E-Cap., Ultra Low Impedance Enabled high ripple current by a reduction of impedance at high frequency. high reliability withstading to 5000hrs load life at 105°C, Long Lead, ROHS Conform, Packing Bulk-Ware into Polybag

Ordering Informations:

Serie-No. / Voltage / Range / Size	Capacity Tolerance	ROHS	Packing
I14057-2501010611	M	R	BU

Serie	Voltage (V)	Range µH)	D * L (mm)	Tolerance Order Code	**R**= ROHS	**BU**= Bulk-Ware Long Lead
					N= NON ROHS	**T/B**= Tape/Box
						L3= Lead-Length 3~3,5mm

Soldering Information

Lead Solder Performance



Lead free Solder Performenace



DRW:	Lexua	CHKD	Wilson	MATL:	ChuChu	DATE	23.12.2024
APPD:	Jimmy			FINISH	Josy	Sheet	2 from 2

Copyright by S.Tiede