



THT, Radial E-Cap., Enabled high ripple current by a reduction of impedance at high frequency range, high reliability withstanding to 10000 hours load life 105°C ,Long Lead, ROHS Conform, Packing Bulk-Ware into Polybag

Items		Performance Characteristics									
Operating temperature range	-40°C +105°C										
Leakage current max.	I = 0,01CV + 3μA whichever is greater (after 2 minutes)										
	I = 0,03CV + 4μA whichever is greater (after 1 minutes)										
Capacitance tolerance	±20% at 120Hz, 20°C										
Dissipation factor max. (at 120Hz, 20°C)	Capacitance > 1000μF ; tanQ increases by 0,02 for each 1000μF from below value.										
	WV		6,3	10	16	25	35	50	63	100	
	TanQ		0,22	0,19	0,16	0,14	0,12	0,10	0,09	0,08	
Low temperature characteristics (Impedance ratio at 120Jz)	Z-40°C / Z+20°C						Z-25°C / Z+20°C				
	3						2				
Load life (after application of the rated voltage for 10000hrs at 105°C)	Leakage Current						Less than specified Value				
	Capacitance Change						Within ±25% off initial Value				
	TanQ						Less than 200% of specified value				
	ø5 , ø6,3 : 6000hours; ø8: 8000hours : ø10 : 10000hours										
Shelf life (at 105°C)	After 1000 hours no load test, leakage current, capacitance and tanQ are same as load life value.										

FREQUENCY COEFFICIENT OF PERMISSIBLE RIPPLE CURRENT

μF	Frequency	120Hz	1kHz	10kHz	50kHz	100kHz≤	
~33		0,42	0,70	0,90	0,95	1,00	
39~270		0,50	0,73	0,92	0,96	1,00	
330~680		0,55	0,77	0,94	0,97	1,00	
820~1800		0,60	0,80	0,96	0,98	1,00	
2200~		0,70	0,50	0,98	0,99	1,00	

Technical Details

Range (μF)	33		ØD(mm)	5,0
Voltage	16		L(mm)	11,0
Impedance (Ω)	0,45		F(mm)	2,0
Ripple Current (mA)	250		Ød(mm)	0,5
ESR (Ω) max.at 20°C 10KHz	-.-		α(mm)	1,5
Lifetime (hrs)	6000		-.-	-.-
Operating- Temperature Range (°C)	-40°C ~ +105°C		-.-	-.-



ØD	5	6,3	8	10	12,5	16	18	
F	2	2,5	3,5	5,0	5,0	7,5	7,5	
Ød	0,5			0,6		0,8		
α	1,5			2.0				

DRW:	Lexua	CHKD	Wilson	MATL:	ChuChu	DATE	23.12.2024
APPD:	Jimmy			FINISH	Josy	Sheet	1 from 2

Copyright by S.Tiede



THT, Radial E-Cap., Enabled high ripple current by a reduction of impedance at high frequency range, high reliability withstanding to 10000 hours load life 105°C ,Long Lead, ROHS Conform, Packing Bulk-Ware into Polybag

Ordering Informations:

Serie-No. / Voltage / Range / Size	Capacity Tolerance	ROHS	Packing
------------------------------------	--------------------	------	---------

I14059-1603300511	M	R	BU
-------------------	---	---	----

Serie	Voltage (V)	Range μ H)	D * L (mm)	Tolerance Order Code	R= ROHS N= NON ROHS	BU= Bulk-Ware Long Lead T/B= Tape/Box L3= Lead-Length 3~3,5mm
-------	-------------	----------------	------------	----------------------	------------------------	---

Soldering Information

Lead Solder Performance



Lead free Solder Performance



DRW:	Lexua	CHKD	Wilson	MATL:	ChuChu	DATE	23.12.2024
APPD:	Jimmy			FINISH	Josy	Sheet	2 from 2