



THT, Radial E-Cap., Enabled high ripple current by a reduction of impedance at high frequency range, high reliability withstanding to 10000 hours load life 105°C ,Long Lead, ROHS Conform, Packing Bulk-Ware into Polybag


Items			Performance Characteristics										
Operating temperature range			-40°C +105°C										
Leakage current max.			I = 0,01CV + 3µA whichever is greater (after 2 minutes)										
			I = 0,03CV + 4µA whichever is greater (after 1 minutes)										
Capacitance tolerance			±20% at 120Hz, 20°C										
Dissipation factor max. (at 120Hz, 20°C)			Capacitance > 1000µF ; tanQ increases by 0,02 for each 1000µF from below value.										
			WV		6,3	10	16	25	35	50	63	100	
			TanQ		0,22	0,19	0,16	0,14	0,12	0,10	0,09	0,08	
Low temperature characteristics (Impedance ratio at 120Jz)			Z-40°C / Z+20°C						Z-25°C / Z+20°C				
			3						2				
Load life (after application of the rated voltage for 10000hrs at 105°C)			Leakage Current						Less than specified Value				
			Capacitance Change						Within ±25% off initial Value				
			TanQ						Less than 200% of specified value				
			ø5 , ø6,3 : 6000hours; ø8: 8000hours : ø10 : 10000hours										
Shelf life (at 105°C)			After 1000 hours no load test, leakage current, capacitance and tanQ are same as load life value.										

FREQUENCY COEFFICIENT OF PERMISSIBLE RIPPLE CURRENT

µF	Frequency	120Hz	1kHz	10kHz	50kHz	100kHz≤	
~33		0,42	0,70	0,90	0,95	1,00	
39~270		0,50	0,73	0,92	0,96	1,00	
330~680		0,55	0,77	0,94	0,97	1,00	
820~1800		0,60	0,80	0,96	0,98	1,00	
2200~		0,70	0,50	0,98	0,99	1,00	

Technical Details

Range (µF)	1500	ØD(mm)	10,0
Voltage	6,3	L(mm)	20,0
Impedance (Ω)	0,027	F(mm)	5,0
Ripple Current (mA)	1820	Ød(mm)	0,6
ESR (Ω) max.at 20°C 10KHz	-.-	α(mm)	2
Lifetime (hrs)	10000	-.-	-.-
Operating- Temperature Range (°C)	-40°C ~ +105°C	-.-	-.-



ØD	5	6,3	8	10	12,5	16	18	
F	2	2,5	3,5	5,0	5,0	7,5	7,5	
Ød	0,5			0,6		0,8		
α	1,5			2.0				

DRW:	Lexua	CHKD	Wilson	MATL:	ChuChu	DATE	23.12.2024
APPD:	Jimmy			FINISH	Josy	Sheet	1 from 2

Copyright by S.Tiede



THT, Radial E-Cap., Enabled high ripple current by a reduction of impedance at high frequency range, high reliability withstanding to 10000 hours load life 105°C ,Long Lead, ROHS Conform, Packing Bulk-Ware into Polybag

Ordering Informations:

Serie-No. / Voltage / Range / Size	Capacity Tolerance	ROHS	Packing
------------------------------------	--------------------	------	---------

I14059-6V31521020	M	R	BU
-------------------	---	---	----

Serie	Voltage (V)	Range μ H)	D * L (mm)	Tolerance Order Code	R= ROHS N= NON ROHS	BU= Bulk-Ware Long Lead T/B= Tape/Box L3= Lead-Length 3~3,5mm
-------	-------------	----------------	------------	----------------------	------------------------	---

Soldering Information

Lead Solder Performance



Lead free Solder Performance



DRW:	Lexua	CHKD	Wilson	MATL:	ChuChu	DATE	23.12.2024
APPD:	Jimmy			FINISH	Josy	Sheet	2 from 2