



THT, Radial E-Cap., Miniature long life for LED Lighting High Reliability, withstanding 10000 hours load life at 105°C , Long Lead, ROHS Conform, Packing Bulk-Ware into Polybag


Items			Performance Characteristics													
Operating temperature range			-25°C +105°C													
Leakage current max.			I = 0,01CV + 3µA whichever is greater (after 2 minutes)													
			I = 0,03CV + 4µA whichever is greater (after 1 minutes)													
Capacitance tolerance			±20% at 120Hz, 20°C													
Dissipation factor max. (at 120Hz, 20°C)																
			WV			10	16	25	35	50	63	100				
			TanQ			0,45	0,35	0,30	0,22	0,19	0,17	0,15				
Low temperature characteristics (Impedance ratio at 120Jz)			WV			10	16	25	35	50	63	100				
			Z-25°C / Z+20°C			8	6	4	4	3	4	4				
Load life (after application of the rated voltage for 10000hrs at 105°C)			Leakage Current							Less than specified Value						
			Capacitance Change							Within ±25% off initial Value						
			TanQ							Less than 200% of specified value						
Shelf life (at 105°C)			After 1000 hours no load test, leakage current, capacitance and tanQ are same as load life value.													

FREQUENCY COEFFICIENT OF PERMISSIBLE RIPPLE CURRENT

µF	Frequency	120Hz	1kHz	10kHz	50kHz	100kHz≤	
~33		0,42	0,70	0,90	0,95	1,00	
47~		0,50	0,73	0,92	0,96	1,00	

Technical Details

Range (µF)	220	ØD(mm)	6,3
Voltage	10	L(mm)	11,0
Impedance (Ω)	-.-	F(mm)	2,5
Ripple Current (mA)	252	Ød(mm)	0,5
ESR (Ω) max.at 20°C 10KHz	-.-	α(mm)	1,5
Lifetime (hrs)	10000	-.-	-.-
Operating- Temperature Range (°C)	-25°C ~ +105°C	-.-	-.-



ØD	5	6,3	8				
F	2	2,5	3,5				
Ød	0,5						
α	1,5						

DRW:	Lexua	CHKD	Wilson	MATL:	ChuChu	DATE	23.12.2024
APPD:	Jimmy			FINISH	Josy	Sheet	1 from 2



THT, Radial E-Cap., Miniature long life for LED Lighting High Reliability, withstanding 10000 hours load life at 105°C , Long Lead, ROHS Conform, Packing Bulk-Ware into Polybag

Ordering Informations:


Serie-No. / Voltage / Range / Size	Capacity Tolerance	ROHS	Packing
------------------------------------	--------------------	------	---------

I14062-1002210611	M	R	BU
-------------------	---	---	----

Serie	Voltage (V)	Range µH)	D * L (mm)	Tolerance Order Code	R= ROHS N= NON ROHS	BU= Bulk-Ware Long Lead T/B= Tape/Box L3= Lead-Length 3~3,5mm
-------	-------------	-----------	------------	----------------------	------------------------	---

Soldering Information

Lead Solder Performance



Lead free Solder Performance



DRW:	Lexua	CHKD	Wilson	MATL:	ChuChu	DATE	23.12.2024
APPD:	Jimmy			FINISH	Josy	Sheet	2 from 2