



**THT, Radial E-Cap., Snap-In, Standard Temp-Range, included 500WV products, Life time 2000 hours, ROHS Conform, Packing Box**

| Items                                                                      |                    | Performance Characteristics                                                                       |      |      |      |      |      |      |      |         |         |         |
|----------------------------------------------------------------------------|--------------------|---------------------------------------------------------------------------------------------------|------|------|------|------|------|------|------|---------|---------|---------|
| Operating temperature range                                                |                    | -40°C +85°C (6,3~315V, -25°C ~ +85°C ( 350~550V)                                                  |      |      |      |      |      |      |      |         |         |         |
| Leakage current max.                                                       |                    | I=3 √cv (µA) (after 5 minutes)                                                                    |      |      |      |      |      |      |      |         |         |         |
|                                                                            |                    |                                                                                                   |      |      |      |      |      |      |      |         |         |         |
| Capacitance tolerance                                                      |                    | ±20% at 120Hz, 20°C                                                                               |      |      |      |      |      |      |      |         |         |         |
| Dissipation factor max.<br>(at 120Hz, 20°C)                                |                    | WV                                                                                                | 6,3  | 10   | 16   | 25   | 35   | 50   | 63   | 80, 100 | 160~400 | 450 550 |
|                                                                            |                    | TanQ                                                                                              | 0,60 | 0,55 | 0,50 | 0,40 | 0,35 | 0,30 | 0,25 | 0,20    | 0,15    | 0,20    |
|                                                                            |                    |                                                                                                   |      |      |      |      |      |      |      |         |         |         |
|                                                                            |                    |                                                                                                   |      |      |      |      |      |      |      |         |         |         |
|                                                                            |                    |                                                                                                   |      |      |      |      |      |      |      |         |         |         |
| Load life ( after application of the<br>rated voltage for 2000hrs at 85°C) | Leakage Current    | Less than specified Value                                                                         |      |      |      |      |      |      |      |         |         |         |
|                                                                            | Capacitance Change | Within ±20% off initial Value                                                                     |      |      |      |      |      |      |      |         |         |         |
|                                                                            | TanQ               | Less than 200% of specified value                                                                 |      |      |      |      |      |      |      |         |         |         |
| Shelf life (at 85°C)                                                       |                    | After 1000 hours no load test, leakage current, capacitance and tanQ are same as load life value. |      |      |      |      |      |      |      |         |         |         |

**FREQUENCY COEFFICIENT OF PERMISSIBLE RIPPLE CURRENT**

| WV        | Frequency | 50HZ | 120Hz | 300Hz | 1kHz |  | 10kHz≤ |
|-----------|-----------|------|-------|-------|------|--|--------|
| ~ 100     |           | 0,85 | 1,00  | 1,06  | 1,15 |  | 1,20   |
| 160 ~ 250 |           | 0,85 | 1,00  | 1,20  | 1,25 |  | 1,45   |
| 315 ~     |           | 0,85 | 1,00  | 1,15  | 1,20 |  | 1,40   |
|           |           |      |       |       |      |  |        |
|           |           |      |       |       |      |  |        |


**Technical Details**

|                                   |                |        |      |
|-----------------------------------|----------------|--------|------|
| Range (µF)                        | 390            | ØD(mm) | 25,0 |
| Voltage                           | 315            | L(mm)  | 40,0 |
| Impedance (Ω)                     | -. -           | F(mm)  | 10,0 |
| Ripple Current (mA)               | 1,86           | Ød(mm) | 0    |
| ESR (Ω) max.at 20°C 10KHz         | #NV            | α(mm)  | 0    |
| Lifetime (hrs)                    | 2000           |        | 2,0  |
| Operating- Temperature Range (°C) | -.40°C ~ +85°C |        | -. - |

ØD≤40



PC Board  
Mounting Holes





Terminal




\* Shorter terminal(4.0±0.5) is also available upon request.  
Terminal length of height 20mm products is applied shorter terminal to standard terminal type.

ØD=35, 40



PC Board  
Mounting Holes



|       |       |      |        |        |        |       |            |
|-------|-------|------|--------|--------|--------|-------|------------|
| DRW:  | Lexua | CHKD | Wilson | MATL:  | ChuChu | DATE  | 11.01.2025 |
| APPD: | Jimmy |      |        | FINISH | Josy   | Sheet | 1 from 2   |

Copyright by S.Tiede



THT, Radial E-Cap., Snap-In, Standard Temp-Range, included 500WV products, Life time 2000 hours, ROHS Conform, Packing Box

### Ordering Informations:

| Serie-No. / Voltage / Range / Size | Capacity Tolerance | ROHS | Packing |
|------------------------------------|--------------------|------|---------|
|------------------------------------|--------------------|------|---------|

|                   |   |   |    |
|-------------------|---|---|----|
| I14078-3113912540 | M | R | BU |
|-------------------|---|---|----|

| Serie | Voltage (V) | Range $\mu$ H) | D * L (mm) | Tolerance Order Code | R= ROHS<br>N= NON ROHS | BU= Bulk-Ware (Box) |
|-------|-------------|----------------|------------|----------------------|------------------------|---------------------|
|       |             |                |            |                      |                        |                     |
|       |             |                |            |                      |                        |                     |

### Soldering Information

#### Lead Solder Performance



#### Lead free Solder Performance



|       |       |      |        |        |        |       |            |
|-------|-------|------|--------|--------|--------|-------|------------|
| DRW:  | Lexua | CHKD | Wilson | MATL:  | ChuChu | DATE  | 11.01.2025 |
| APPD: | Jimmy |      |        | FINISH | Josy   | Sheet | 2 from 2   |