EDCON COMPONENTS
A MEMBER OF EDCON-GROUP

THT, Radial E-Cap., Snap-In, High Voltage, High Capacitance, Load Life of 3000 hrs at 85°C, ROHS Conform, Packing Box

Items	Performance Characteristics
Operating temperature range	.-40°C +85°C (10~250V, -25°C ~ +85°C (350~500V)
Leakage currrent max.	I=3 √cv (µA) (after 5 minutes)

Dissipation factor max. (at 120Hz, 20°C)	WV	10	16	25	35	50	63	80, 100	160~400	450~500
	TanQ	0,55	0,50	0,40	0,35	0,30	0,25	0,20	0,15	0,20

Load life (after application of the rated voltage for 3000hrs at 85°C)		
	Leckage Current	Less than specified Value
	Capacitance Change	Within ±20% off initial Value
	TanQ	Less than 200% of specified value
Shelf life (at 85°C)	After 1000 hours no load test, leackage current, capacitance and tanQ are same as load life value.	

FREQUENY COEFFICIENT OF PERMISSIBLE RIPPE CURRENT

WV	Frequency	50HZ	120Hz	300Hz	1kHz		10kHz≤
~ 100		0,85	1,00	1,06	1,15		1,20
160 ~ 250		0,85	1,00	1,20	1,25		1,45
350 ~		0,85	1,00	1,15	1,20		1,40

Technical Details

Range (µF)	8200	ØD(mm)	35,0
Voltage	63	L(mm)	35,0
Impedance (Ω)	-.-	F(mm)	10,0
Ripple Current (mA)	4,99	Ød(mm)	0
ESR (Ω) max.at 20°C 10KHz	-.-	α(mm)	0
Lifetime (hrs)	3000	-.-	2,0
Operating- Temperature Range (°C)	.-40°C ~ +85°C	-.-	-.-

ØD≤40



* Shorter terminal(4.0±0.5) is also available upon request.
Terminal length of height 20mm products is applied shorter terminal to standard terminal type.

ØD=35, 40



DRW:	Lexua	CHKD	Wilson	MATL:	ChuChu	DATE	03.02.2025
APPD:	Jimmy			FINISH	Josy	Sheet	1 from 2

Copyright by S.Tiede

THT, Radial E-Cap., Snap-In, High Voltage, High Capacitance, Load Life of 3000 hrs at 85°C, ROHS Conform, Packing Box

Ordering Informations:

Serie-No. / Voltage / Range / Size	Capacity Tolerance	ROHS	Packing
I14079-6308223535	M	R	BU

Serie	Voltage (V)	Range µH)	D * L (mm)	Tolerance Order Code	**R**= ROHS	**BU**= Bulk-Ware (Box)
					N= NON ROHS	

Soldering Information

Lead Solder Performance



Lead free Solder Performenace



DRW:	Lexua	CHKD	Wilson	MATL:	ChuChu	DATE	03.02.2025
APPD:	Jimmy			FINISH	Josy	Sheet	2 from 2

Copyright by S.Tiede