



THT, Radial E-Cap., Snap-In, Long Life, Load Life of 5000hrs, at 105°C , ROHS Conform, Packing Box

Items		Performance Characteristics										
Operating temperature range		-40°C +105°C (10~250V, -25°C ~ +105°C (350~500V)										
Leakage current max.		I=3 √cv (μA) (after 5 minutes)										
Capacitance tolerance		±20% at 120Hz, 20°C										
Dissipation factor max. (at 120Hz, 20°C)	WV		10	16	25	35	50	63	80, 100	160~400	450~500	
	TanQ		0,55	0,50	0,40	0,35	0,30	0,25	0,20	0,15	0,20	
Load life (after application of the rated voltage for 5000hrs at 105°C)	Leakage Current	Less than specified Value										
	Capacitance Change	Within ±25% off initial Value										
	TanQ	Less than 250% of specified value										
Shelf life (at 105°C)		After 1000 hours no load test, leakage current, capacitance and tanQ are same as load life value.										

FREQUENCY COEFFICIENT OF PERMISSIBLE RIPPLE CURRENT

WV	Frequency	50HZ	120Hz	300Hz	1kHz		10kHz≤
~ 100		0,85	1,00	1,06	1,15		1,20
160 ~ 250		0,85	1,00	1,20	1,25		1,45
350 ~		0,85	1,00	1,15	1,20		1,40

Technical Details


Range (μF)	220	ØD(mm)	35,0
Voltage	500	L(mm)	30,0
Impedance (Ω)	-. -	F(mm)	10,0
Ripple Current (mA)	1,51	Ød(mm)	0
ESR (Ω) max.at 20°C 10KHz	-. -	α(mm)	0
Lifetime (hrs)	5000		2,0
Operating- Temperature Range (°C)	-.25°C ~ +105°C		-. -

ØD≤40





PC Board
Mounting Holes

Terminal




* Shorter terminal(4.0±0.5) is also available upon request.
Terminal length of height 20mm products is applied shorter terminal to standard terminal type.

ØD=35, 40



PC Board
Mounting Holes



DRW:	Lexua	CHKD	Wilson	MATL:	ChuChu	DATE	15.01.2025
APPD:	Jimmy			FINISH	Josy	Sheet	1 from 2

Copyright by S.Tiede



THT, Radial E-Cap., Snap-In, Long Life, Load Life of 5000hrs, at 105°C , ROHS Conform, Packing Box

Ordering Informations:

Serie-No. / Voltage / Range / Size	Capacity Tolerance	ROHS	Packing
------------------------------------	--------------------	------	---------

I14085-5012213530	M	R	BU
-------------------	---	---	----

Serie	Voltage (V)	Range μ H)	D * L (mm)	Tolerance Order Code	R= ROHS N= NON ROHS	BU= Bulk-Ware (Box)

Soldering Information

Lead Solder Performance



Lead free Solder Performance



DRW:	Lexua	CHKD	Wilson	MATL:	ChuChu	DATE	15.01.2025
APPD:	Jimmy			FINISH	Josy	Sheet	2 from 2