



**THT, Radial E-Cap., Snap-In, Long Life, Load Life 10000 hours at 105°C, Voltage Range of 400V~500V, Suited for use in industrial power suppliers where high reliability, ROHS Conform, Packing Box**

| Items                                                                           |                    | Performance Characteristics                                                                       |  |  |  |  |      |      |      |  |  |
|---------------------------------------------------------------------------------|--------------------|---------------------------------------------------------------------------------------------------|--|--|--|--|------|------|------|--|--|
| Operating temperature range                                                     |                    | -25°C +105°C                                                                                      |  |  |  |  |      |      |      |  |  |
| Leakage current max.                                                            |                    | I=3 √cv (μA) (after 5 minutes)                                                                    |  |  |  |  |      |      |      |  |  |
|                                                                                 |                    |                                                                                                   |  |  |  |  |      |      |      |  |  |
| Capacitance tolerance                                                           |                    | ±20% at 120Hz, 20°C                                                                               |  |  |  |  |      |      |      |  |  |
| Dissipation factor max.<br>(at 120Hz, 20°C)                                     | WV                 |                                                                                                   |  |  |  |  | 400  | 450  | 500  |  |  |
|                                                                                 | TanQ               |                                                                                                   |  |  |  |  | 0,15 | 0,20 | 0,20 |  |  |
|                                                                                 |                    |                                                                                                   |  |  |  |  |      |      |      |  |  |
|                                                                                 |                    |                                                                                                   |  |  |  |  |      |      |      |  |  |
| Load life ( after application of the<br>rated voltage for 10000hrs at<br>105°C) | Leakage Current    | Less than specified Value                                                                         |  |  |  |  |      |      |      |  |  |
|                                                                                 | Capacitance Change | Within ±30% off initial Value                                                                     |  |  |  |  |      |      |      |  |  |
|                                                                                 | TanQ               | Less than 300% of specified value                                                                 |  |  |  |  |      |      |      |  |  |
|                                                                                 |                    |                                                                                                   |  |  |  |  |      |      |      |  |  |
| Shelf life (at 105°C)                                                           |                    | After 1000 hours no load test, leakage current, capacitance and tanQ are same as load life value. |  |  |  |  |      |      |      |  |  |



#### FREQUENCY COEFFICIENT OF PERMISSIBLE RIPPLE CURRENT

| WV        | Frequency | 50HZ | 120Hz | 300Hz | 1kHz |  | 10kHz≤ |
|-----------|-----------|------|-------|-------|------|--|--------|
| 400 ~ 500 |           | 0,85 | 1,00  | 1,15  | 1,20 |  | 1,40   |
|           |           |      |       |       |      |  |        |
|           |           |      |       |       |      |  |        |
|           |           |      |       |       |      |  |        |
|           |           |      |       |       |      |  |        |

#### Technical Details


|                                   |                |        |      |
|-----------------------------------|----------------|--------|------|
| Range (μF)                        | 270            | ØD(mm) | 35,0 |
| Voltage                           | 400            | L(mm)  | 30,0 |
| Impedance (Ω)                     | -.-            | F(mm)  | 10,0 |
| Ripple Current (mA)               | 1,26           | Ød(mm) | 0    |
| ESR (Ω) max.at 20°C 10KHz         | -.-            | α(mm)  | 0    |
| Lifetime (hrs)                    | 10000          | -.-    | 2,0  |
| Operating- Temperature Range (°C) | -25°C ~ +105°C | -.-    | -.-  |

ØD≤40





PC Board  
Mounting Holes

Terminal




\* Shorter terminal(4.0±0.5) is also available upon request.  
Terminal length of height 20mm products is applied shorter terminal to standard terminal type.

ØD=35, 40



PC Board  
Mounting Holes



|       |       |      |        |        |        |       |            |
|-------|-------|------|--------|--------|--------|-------|------------|
| DRW:  | Lexua | CHKD | Wilson | MATL:  | ChuChu | DATE  | 15.01.2025 |
| APPD: | Jimmy |      |        | FINISH | Josy   | Sheet | 1 from 2   |

Copyright by S.Tiede



THT, Radial E-Cap., Snap-In, Long Life, Load Life 10000 hours at 105°C, Voltage Range of 400V~500V, Suited for use in industrial power suppliers where high reliability, ROHS Conform, Packing Box

### Ordering Informations:


| Serie-No. / Voltage / Range / Size | Capacity Tolerance | ROHS | Packing |
|------------------------------------|--------------------|------|---------|
|------------------------------------|--------------------|------|---------|

|                   |   |   |    |
|-------------------|---|---|----|
| I14087-4012713530 | M | R | BU |
|-------------------|---|---|----|


| Serie | Voltage (V) | Range $\mu$ H) | D * L (mm) | Tolerance Order Code | R= ROHS<br>N= NON ROHS | BU= Bulk-Ware (Box) |
|-------|-------------|----------------|------------|----------------------|------------------------|---------------------|
|       |             |                |            |                      |                        |                     |
|       |             |                |            |                      |                        |                     |

### Soldering Information

#### Lead Solder Performance



#### Lead free Solder Performance



|       |       |      |        |        |        |       |            |
|-------|-------|------|--------|--------|--------|-------|------------|
| DRW:  | Lexua | CHKD | Wilson | MATL:  | ChuChu | DATE  | 15.01.2025 |
| APPD: | Jimmy |      |        | FINISH | Josy   | Sheet | 2 from 2   |