



THT, Radial E-Cap., Snap-In, Long Life, Load Life 10000 hours at 105°C, Voltage Range of 400V~500V, Suited for use in industrial power suppliers where high reliability, ROHS Conform, Packing Box

Items		Performance Characteristics									
Operating temperature range		-25°C +105°C									
Leakage current max.		I=3 √cv (μA) (after 5 minutes)									
Capacitance tolerance		±20% at 120Hz, 20°C									
Dissipation factor max. (at 120Hz, 20°C)	WV						400	450	500		
	TanQ						0,15	0,20	0,20		
Load life (after application of the rated voltage for 10000hrs at 105°C)	Leakage Current	Less than specified Value									
	Capacitance Change	Within ±30% off initial Value									
	TanQ	Less than 300% of specified value									
Shelf life (at 105°C)		After 1000 hours no load test, leakage current, capacitance and tanQ are same as load life value.									



FREQUENCY COEFFICIENT OF PERMISSIBLE RIPPLE CURRENT

WV	Frequency	50HZ	120Hz	300Hz	1kHz		10kHz≤
400 ~ 500		0,85	1,00	1,15	1,20		1,40

Technical Details


Range (μF)	270	ØD(mm)	35,0
Voltage	500	L(mm)	50,0
Impedance (Ω)	-. -	F(mm)	10,0
Ripple Current (mA)	0,92	Ød(mm)	0
ESR (Ω) max.at 20°C 10KHz	-. -	α(mm)	0
Lifetime (hrs)	10000		2,0
Operating- Temperature Range (°C)	-.25°C ~ +105°C		-. -

ØD≤40





PC Board
Mounting Holes

Terminal




* Shorter terminal(4.0±0.5) is also available upon request.
Terminal length of height 20mm products is applied shorter terminal to standard terminal type.

ØD=35, 40



PC Board
Mounting Holes



DRW:	Lexua	CHKD	Wilson	MATL:	ChuChu	DATE	15.01.2025
APPD:	Jimmy			FINISH	Josy	Sheet	1 from 2

Copyright by S.Tiede



THT, Radial E-Cap., Snap-In, Long Life, Load Life 10000 hours at 105°C, Voltage Range of 400V~500V, Suited for use in industrial power suppliers where high reliability, ROHS Conform, Packing Box

Ordering Informations:

Serie-No. / Voltage / Range / Size	Capacity Tolerance	ROHS	Packing
------------------------------------	--------------------	------	---------

I14087-5012713550	M	R	BU
-------------------	---	---	----

Serie	Voltage (V)	Range μ H)	D * L (mm)	Tolerance Order Code	R= ROHS N= NON ROHS	BU= Bulk-Ware (Box)

Soldering Information

Lead Solder Performance



Lead free Solder Performance



DRW:	Lexua	CHKD	Wilson	MATL:	ChuChu	DATE	15.01.2025
APPD:	Jimmy			FINISH	Josy	Sheet	2 from 2