



THT, Radial E-Cap., Enabled high ripple current by a reduction of impedance at high frequency, high reliability withstanding, for switching power supplies, noise filter, adapter, charger, Long Lead, ROHS Conform, Packing Bulk-Ware into Polybag

Items			Performance Characteristics											
Operating temperature range			-40°C +105°C											
Leakage current max.														
			I = 0,01CV or 3µA whichever is greater (after 2 minutes)											
Capacitance tolerance			±20% at 120Hz, 20°C											
Dissipation factor max. (at 120Hz, 20°C)			Capacitance > 1000µF ; tanQ increases by 0,02 for each 1000µF from below value.											
			WV	6,3	10	16	25	35	50	63	100			
			TanQ	0,22	0,19	0,16	0,14	0,12	0,10	0,09	0,08			
Low temperature characteristics (Impedance ratio at 120Jz)														
		Z-25°C / Z+20°C	2											
		Z-40°C / Z+20°C	3											
Load life (after application of the rated voltage for 5000hrs at 105°C)			Leakage Current						Less than specified Value					
			Capacitance Change						Within ±20% of initial value					
			TanQ						Less than 200% of specified value					
Shelf life (at 105°C)			After 1000 hours no load test, leakage current, capacitance and tanQ are same as load life value.											
Ø5, Ø6,3 : 2000Hours, Ø8: 3000Hours, Ø10:5000hours														


Ø5, Ø6,3 : 2000Hours, Ø8: 3000Hours, Ø10:5000hours

FREQUENCY COEFFICIENT OF PERMISSIBLE RIPPE CURRENT

µF/Frequency	120Hz	1kHz	10kHz	100kHz≤
~33	0,42	0,70	0,90	1,00
47~220	0,50	0,73	0,92	1,00
330~680	0,55	0,75	0,94	1,00
1000~1500	0,60	0,80	0,96	1,00
2200~15000	0,70	0,85	0,98	1,00

Technical Details

Range (µF)	0,47	ØD(mm)	5,0
Voltage	50	L(mm)	11,0
Impedance (Ω)	3,85	F(mm)	2,0
Ripple Current (mA)	140	Ød(mm)	0,5
ESR (Ω) max.at 20°C 10KHz	-.-	α(mm)	1,5
Lifetime (hrs)	2000	-.-	-.-
Operating- Temperature Range (°C)	-40°C ~ +105°C	-.-	-.-



ØD	5	6,3	8	10	12,5	16	18
F	2	2,5	3,5	5,0	5,0	7,5	7,5
ØD	0,5			0,6		0,8	
α	1,5			2,0			

DRW:	Lexua	CHKD	Wilson	MATL:	ChuChu	DATE	17.01.2025
APPD:	Jimmy			FINISH	Josy	Sheet	1 from 2

Copyright by S.Tiede



THT, Radial E-Cap., Enabled high ripple current by a reduction of impedance at high frequency, high reliability withstanding, for switching power supplies, noise filter, adapter, charger, Long Lead, ROHS Conform, Packing Bulk-Ware into Polybag

Ordering Informations:


Serie-No. / Voltage / Range / Size	Capacity Tolerance	ROHS	Packing
------------------------------------	--------------------	------	---------

I14112-500R470511	M	R	BU
-------------------	---	---	----

Serie	Voltage (V)	Range μ H)	D * L (mm)	Tolerance Order Code	R= ROHS	BU= Bulk-Ware Long Lead
					N= NON ROHS	T/B= Tape/Box
						L3= Lead-Length 3~3,5mm

Soldering Information

Lead Solder Performance



Lead free Solder Performance



DRW:	Lexua	CHKD	Wilson	MATL:	ChuChu	DATE	17.01.2025
APPD:	Jimmy			FINISH	Josy	Sheet	2 from 2