



**THT, Radial E-Cap., Enabled high ripple current by a reduction of impedance at high frequency, High reliability withstanding, for switching power supplies, noise filter, adapter, charger, Long Lead, ROHS Conform, Packing Bulk-Ware into Polybag**


| Items                                                                           |                 |                                                                                                   | Performance Characteristics |      |      |      |      |                                   |      |      |  |  |  |
|---------------------------------------------------------------------------------|-----------------|---------------------------------------------------------------------------------------------------|-----------------------------|------|------|------|------|-----------------------------------|------|------|--|--|--|
| Operating temperature range                                                     |                 | -40°C +105°C                                                                                      |                             |      |      |      |      |                                   |      |      |  |  |  |
| Leakage current max.                                                            |                 |                                                                                                   |                             |      |      |      |      |                                   |      |      |  |  |  |
|                                                                                 |                 | I = 0,01CV or 3µA whichever is greater (after 2 minutes)                                          |                             |      |      |      |      |                                   |      |      |  |  |  |
|                                                                                 |                 |                                                                                                   |                             |      |      |      |      |                                   |      |      |  |  |  |
| Capacitance tolerance                                                           |                 | ±20% at 120Hz, 20°C                                                                               |                             |      |      |      |      |                                   |      |      |  |  |  |
| Dissipation factor max.<br>(at 120Hz, 20°C)                                     |                 | Capacitance > 1000µF ; tanQ increases by 0,02 for each 1000µF from below value.                   |                             |      |      |      |      |                                   |      |      |  |  |  |
|                                                                                 |                 | WV                                                                                                | 6,3                         | 10   | 16   | 25   | 35   | 50                                | 63   | 100  |  |  |  |
|                                                                                 |                 | TanQ                                                                                              | 0,22                        | 0,19 | 0,16 | 0,14 | 0,12 | 0,10                              | 0,09 | 0,08 |  |  |  |
| Low temperature<br>characteristics (Impedance<br>ratio at 120Jz)                |                 |                                                                                                   |                             |      |      |      |      |                                   |      |      |  |  |  |
|                                                                                 | Z-25°C / Z+20°C | 2                                                                                                 |                             |      |      |      |      |                                   |      |      |  |  |  |
|                                                                                 | Z-40°C / Z+20°C | 3                                                                                                 |                             |      |      |      |      |                                   |      |      |  |  |  |
| Load life ( after application of the<br>rated voltage for 10000hrs at<br>105°C) |                 | Leakage Current                                                                                   |                             |      |      |      |      | Less than specified Value         |      |      |  |  |  |
|                                                                                 |                 | Capacitance Change                                                                                |                             |      |      |      |      | Within ±25% of initial value      |      |      |  |  |  |
|                                                                                 |                 | TanQ                                                                                              |                             |      |      |      |      | Less than 200% of specified value |      |      |  |  |  |
| Shelf life (at 105°C)                                                           |                 | After 1000 hours no load test, leakage current, capacitance and tanQ are same as load life value. |                             |      |      |      |      |                                   |      |      |  |  |  |
|                                                                                 |                 | Ø5, Ø6,3 : 5000Hours, Ø8 , Ø10:7000hours                                                          |                             |      |      |      |      |                                   |      |      |  |  |  |

**FREQUENCY COEFFICIENT OF PERMISSIBLE RIPPLE CURRENT**

| µF/Frequency | 120Hz | 1kHz | 10kHz | 100kHz≤ |
|--------------|-------|------|-------|---------|
| ~33          | 0,42  | 0,70 | 0,90  | 1,00    |
| 47~220       | 0,50  | 0,73 | 0,92  | 1,00    |
| 330~680      | 0,55  | 0,75 | 0,94  | 1,00    |
| 1000~1500    | 0,60  | 0,80 | 0,96  | 1,00    |
| 2200~15000   | 0,70  | 0,85 | 0,98  | 1,00    |

**Technical Details**

|                                   |                |        |      |
|-----------------------------------|----------------|--------|------|
| Range (µF)                        | 47             | ØD(mm) | 8,0  |
| Voltage                           | 63             | L(mm)  | 11,5 |
| Impedance (Ω)                     | 0,39           | F(mm)  | 3,5  |
| Ripple Current (mA)               | 415            | Ød(mm) | 0,5  |
| ESR (Ω) max.at 20°C 10KHz         | -.-            | α(mm)  | 1,5  |
| Lifetime (hrs)                    | 7000           | -.-    | -.-  |
| Operating- Temperature Range (°C) | -40°C ~ +105°C | -.-    | -.-  |



|    |     |     |     |     |      |     |     |
|----|-----|-----|-----|-----|------|-----|-----|
| ØD | 5   | 6,3 | 8   | 10  | 12,5 | 16  | 18  |
| F  | 2,0 | 2,5 | 3,5 | 5,0 | 5,0  | 7,5 | 7,5 |
| Ød | 0,5 |     |     | 0,6 |      | 0,8 |     |
| α  | 1,5 |     |     | 2,0 |      |     |     |

|       |       |      |        |        |        |       |            |
|-------|-------|------|--------|--------|--------|-------|------------|
| DRW:  | Lexua | CHKD | Wilson | MATL:  | ChuChu | DATE  | 28.01.2025 |
| APPD: | Jimmy |      |        | FINISH | Josy   | Sheet | 1 from 2   |



THT, Radial E-Cap., Enabled high ripple current by a reduction of impedance at high frequency, High reliability withstanding, for switching power supplies, noise filter, adapter, charger, Long Lead, ROHS Conform, Packing Bulk-Ware into Polybag

### Ordering Informations:


| Serie-No. / Voltage / Range / Size | Capacity Tolerance | ROHS | Packing |
|------------------------------------|--------------------|------|---------|
|------------------------------------|--------------------|------|---------|

|                   |   |   |    |
|-------------------|---|---|----|
| I14113-6304700812 | M | R | BU |
|-------------------|---|---|----|

| Serie | Voltage (V) | Range $\mu$ H) | D * L (mm) | Tolerance Order Code | R= ROHS     | BU= Bulk-Ware Long Lead |
|-------|-------------|----------------|------------|----------------------|-------------|-------------------------|
|       |             |                |            |                      | N= NON ROHS | T/B= Tape/Box           |
|       |             |                |            |                      |             | L3= Lead-Length 3~3,5mm |

### Soldering Information

#### Lead Solder Performance



#### Lead free Solder Performance



|       |       |      |        |        |        |       |            |
|-------|-------|------|--------|--------|--------|-------|------------|
| DRW:  | Lexua | CHKD | Wilson | MATL:  | ChuChu | DATE  | 28.01.2025 |
| APPD: | Jimmy |      |        | FINISH | Josy   | Sheet | 2 from 2   |