



**THT, Radialer E-Cap., Extremely lower Impedance, Wide Temperatur-Range +105°C, Life-Time 10000Hrs.
Long Lead, ROHS Conform, Packing Bulk-Ware into Polybag**

Items		Performance Characteristics										
Operating temperature range		-40°C +105°C										
Leakage current max.												
		I = 0,01CV or 3µA whichever is greater (after 2 minutes)										
Capacitance tolerance		±20% at 120Hz, 20°C										
Dissipation factor max. (at 120Hz, 20°C)		Capacitance > 1000µF ; tanQ increases by 0,02 for each 1000µF from below value.										
		WV	6,3	10	16	25	35	50	63	100		
		TanQ	0,22	0,19	0,16	0,14	0,12	0,10	0,09	0,08		
Low temperature characteristics (Impedance ratio at 120Jz)												
	Z-25°C / Z+20°C	2										
	Z-40°C / Z+20°C	3										
Load life (after application of the rated voltage for 10000hrs at 105°C)		Leakage Current					Less than specified Value					
		Capacitance Change					Within ±0% of initial value					
		TanQ					Less than 200% of specified value					
Shelf life (at 105°C)		After 1000 hours no load test, leakage current, capacitance and tanQ are same as load life value.										
Ø5, Ø6,3 : 5000Hours, Ø8, Ø10:7000hours												

FREQUENCY COEFFICIENT OF PERMISSIBLE RIPPLE CURRENT

	µF/Frequency	120Hz	1kHz	10kHz	100kHz≤
	~33	0,42	0,70	0,90	1,00
	47~220	0,50	0,73	0,92	1,00
	330~680	0,55	0,77	0,94	1,00
	1000~1500	0,60	0,80	0,96	1,00
	2200~15000	0,70	0,85	0,98	1,00

Technical Details

Range (µF)	33	ØD(mm)	5,0
Voltage (V)	6,3	L(mm)	11,0
Impedance (Ω)	0,58	F(mm)	2,0
Ripple Current (mA)	215	Ød(mm)	0,5
ESR (Ω) max.at 20°C 10KHz	-.-	α(mm)	1,5
Lifetime (hrs)	5000	-.-	-.-
Operating- Temperature Range (°C)	-40°C ~ +105°C	-.-	-.-



DRW:	Lexua	CHKD	Wilson	MATL:	ChuChu	DATE	04.10.2024
APPD:	Jimmy			FINISH	Josy	Sheet	1 from 2



**THT, Radialer E-Cap., Extremely lower Impedance, Wide Temperatur-Range +105°C, Life-Time 10000Hrs.
Long Lead, ROHS Conform, Packing Bulk-Ware into Polybag**

Ordering Informations:

Serie-No. / Voltage / Range / Size	Capacity Tolerance	ROHS	Packing
------------------------------------	--------------------	------	---------

I14113-6V33300511	M	R	BU
-------------------	---	---	----

Serie	Voltage (V)	Range μ H)	D * L (mm)	Tolerance Order Code	R= ROHS N= NON ROHS	BU= Bulk-Ware Long Lead T/B= Tape/Box L3= Lead-Length 3~3,5mm
-------	-------------	----------------	------------	----------------------	------------------------	---

Soldering Information

Lead Solder Performance



Lead free Solder Performance



DRW:	Lexua	CHKD	Wilson	MATL:	ChuChu	DATE	04.10.2024
APPD:	Jimmy			FINISH	Josy	Sheet	2 from 2