



**THT, Radial E-Cap., Snap-In, Long Life, Low Impedance. Highly ripple, High Reliability, Load Life 5000 hours at 105°C , ROHS Conform, Packing Box**

| Items                                                                          |                    | Performance Characteristics                                |      |      |      |      |      |                                   |         |         |      |
|--------------------------------------------------------------------------------|--------------------|------------------------------------------------------------|------|------|------|------|------|-----------------------------------|---------|---------|------|
| Operating temperature range                                                    |                    | -40°C ~ +105°C (10V ~ 250V); -25°C ~ +105°C ( 350V ~ 450V) |      |      |      |      |      |                                   |         |         |      |
| Leakage current max.                                                           |                    |                                                            |      |      |      |      |      |                                   |         |         |      |
|                                                                                |                    | I = 3√CV μA (after 5 minutes)                              |      |      |      |      |      |                                   |         |         |      |
|                                                                                |                    |                                                            |      |      |      |      |      |                                   |         |         |      |
| Capacitance tolerance                                                          |                    | ±20% at 120Hz, 20°C                                        |      |      |      |      |      |                                   |         |         |      |
| Dissipation factor max.<br>(at 120Hz, 20°C)                                    |                    |                                                            |      |      |      |      |      |                                   |         |         |      |
|                                                                                |                    | WV                                                         | 10   | 16   | 25   | 35   | 50   | 63                                | 80, 100 | 160~400 | 450  |
|                                                                                |                    | TanQ                                                       | 0,55 | 0,50 | 0,40 | 0,35 | 0,30 | 0,25                              | 0,20    | 0,15    | 0,20 |
|                                                                                |                    |                                                            |      |      |      |      |      |                                   |         |         |      |
|                                                                                |                    |                                                            |      |      |      |      |      |                                   |         |         |      |
|                                                                                |                    |                                                            |      |      |      |      |      |                                   |         |         |      |
| Load life ( after application of the<br>rated voltage for 5000hrs at<br>105°C) | Leckage Current    |                                                            |      |      |      |      |      | Less than specified Value         |         |         |      |
|                                                                                | Capacitance Change |                                                            |      |      |      |      |      | Within ±20% off initial Value     |         |         |      |
|                                                                                | TanQ               |                                                            |      |      |      |      |      | Less than 200% of specified value |         |         |      |
| Shelf life (at 105°C)                                                          | Leckage Current    |                                                            |      |      |      |      |      | Less than specified Value         |         |         |      |
|                                                                                | Capacitance Change |                                                            |      |      |      |      |      | Within ±20% off initial Value     |         |         |      |
|                                                                                | TanQ               |                                                            |      |      |      |      |      | Less than 200% of specified value |         |         |      |

**FREQUENCY COEFFICIENT OF PERMISSIBLE RIPPLE CURRENT**

| WV        | Frequency | 50HZ | 120Hz | 300Hz | 1kHz |  | 10kHz≤ |
|-----------|-----------|------|-------|-------|------|--|--------|
| 10 ~ 100  |           | 0,90 | 1,00  | 1,06  | 1,15 |  | 1,25   |
| 160 ~ 250 |           | 0,85 | 1,00  | 1,20  | 1,25 |  | 1,45   |
| 350 ~ 450 |           | 0,85 | 1,00  | 1,15  | 1,20 |  | 1,40   |
|           |           |      |       |       |      |  |        |
|           |           |      |       |       |      |  |        |


**Technical Details**

|                                   |                |        |      |
|-----------------------------------|----------------|--------|------|
| Range (μF)                        | 18000          | ØD(mm) | 35,0 |
| Voltage                           | 35             | L(mm)  | 45,0 |
| Impedance (Ω)                     | 0,018          | F(mm)  | 10,0 |
| Ripple Current (mA)               | 4,3            | Ød(mm) | 0    |
| ESR (Ω) max.at 20°C 10KHz         | 0,017          | α(mm)  | 0    |
| Lifetime (hrs)                    | 5000           | -.-    | 2,0  |
| Operating- Temperature Range (°C) | -40°C ~ +105°C | -.-    | -.-  |

**DRAWING**


Unit : mm

ØD ≤ 40





PC Board Mounting Holes

Terminal




\* Shorter terminal (4.0 ± 0.5) is also available upon request.  
Terminal length of height 20mm products is applied shorter terminal to standard terminal type.

ØD = 35, 40



PC Board Mounting Holes



|       |       |      |        |        |        |       |            |
|-------|-------|------|--------|--------|--------|-------|------------|
| DRW:  | Lexua | CHKD | Wilson | MATL:  | ChuChu | DATE  | 28.01.2025 |
| APPD: | Jimmy |      |        | FINISH | Josy   | Sheet | 1 from 2   |

Copyright by S.Tiede



THT, Radial E-Cap., Snap-In, Long Life, Low Impedance. Highly ripple, High Reliability, Load Life 5000 hours at 105°C , ROHS Conform, Packing Box

### Ordering Informations:

| Serie-No. / Voltage / Range / Size | Capacity Tolerance | ROHS | Packing |
|------------------------------------|--------------------|------|---------|
|------------------------------------|--------------------|------|---------|

|                   |   |   |    |
|-------------------|---|---|----|
| I14125-3501833545 | M | R | BU |
|-------------------|---|---|----|

| Serie | Voltage (V) | Range $\mu$ H) | D * L (mm) | Tolerance Order Code | R= ROHS<br>N= NON ROHS | BU= Bulk-Ware (Box) |
|-------|-------------|----------------|------------|----------------------|------------------------|---------------------|
|       |             |                |            |                      |                        |                     |
|       |             |                |            |                      |                        |                     |

### Soldering Information

#### Lead Solder Performance



#### Lead free Solder Performance



|       |       |      |        |        |        |       |            |
|-------|-------|------|--------|--------|--------|-------|------------|
| DRW:  | Lexua | CHKD | Wilson | MATL:  | ChuChu | DATE  | 28.01.2025 |
| APPD: | Jimmy |      |        | FINISH | Josy   | Sheet | 2 from 2   |