



EDCON-COMPONENTS



Drawing



P.C.B. Layout



A [mm]	
2P	10.0

Specification

Electrical

Standard	
Rated voltage	AC 300V
Rated current	16A
Wire range	22-14 AWG

Mechanical

Ambient temperature	-40°C ~ +105°C
Screw, Torque	M3, 0.45Nm (4.0lb-In.)

Dimensions

Pitch	5.00mm
Poles	2P

Material

Housing	PA66 (UL94V-0)
Pin header	Brass, Tin-plated
Screw	steel, Zinc-plated
Wire guard	Phosphor Bronze, Tin plated



Wire Protector Terminal Block /
Pitch 5.00mm

Part No.: A12L035

DRW:	Bill	CHKD	Lord	MATL:	Jimmy	TOLERANCE	Sam	DATE	14.03.2009
APPD:	Louis			FINISH	Georg			Sheet No.	1 from 3

Customer:

www.edcon-components.com

email: info@edcon-components.com

EDCON-COMPONENTS




Ordering Informations

Serie	-	No. of Pole	Body-Color	wire protector	Screw	-	Customer Request
A12L035	-	XX	XX	X	X	-	X


XX = total	WH - white	1 - with wire protector	A - Slotted screw
02	GN - green	2 - without wire protector	B - Cross-slotted screw (<i>standard</i>)
	GR - gray		
	LG - light gray		



PG - Phoenix Green
OR - orange
BK - black
BL - blue (<i>standard</i>)



wire protector



without wire protector



Wire Protector Terminal Block /
Pitch 5.00mm

Part No.: A12L035

DRW:	Bill	CHKD	Lord	MATL:	Jimmy	TOLERANCE	Sam	DATE	14.03.2009
APPD:	Louis			FINISH	Georg		Sheet No.		2 from 3

Customer:


www.edcon-components.com

email: info@edcon-components.com



Soldering - Profil

Classification Reflow Profile (JEDEC J-STD-020C)



Wire Protector Terminal Block /
Pitch 5.00mm

Part No.: A12L035

DRW:	Bill	CHKD	Lord	MATL:	Jimmy	TOLERANCE	Sam	DATE	14.03.2009
APPD:	Louis			FINISH	Georg		Sheet No.	3 from 3	

Customer: