



# EDCON-COMPONENTS



## Drawing



## P.C.B. Layout



## Specification

APPROVAL		UL <sup>us</sup>	VDE
<b>Electrical</b>			
Standard		UL	IEC
Rated voltage		300V	320V
Rated current		15A	10A
Withstanding voltage		AC 2500V/1min	
<b>Mechanical</b>			
Ambient temperature		-40°C ~ +105°C	
<b>Dimensions</b>			
Pitch		5.00mm	
Poles		2 x (2P - 24P)	
<b>Material</b>			
Housing		PA66 (UL94V-0)	
Pin header		Brass, Tin plated	



## Certification



Pluggable Terminal Block /  
Pitch 5.00mm

Part No.: A14L046

Customer:

DRW:	Bill	CHKD	Lord	MATL:	Jimmy	TOLERANCE	Sam	DATE	14.3.2009
APPD:	Louis			FINISH	Georg		Sheet No.		1 from 3

[www.edcon-components.com](http://www.edcon-components.com)

email: [info@edcon-components.com](mailto:info@edcon-components.com)

# EDCON-COMPONENTS



## Ordering Informations

Serie	-	No. of Pole	Body-Color	-	Customer Request
<b>A14L046</b>	-	<b>XX</b>	<b>XX</b>	-	<b>X</b>

XX = total	<b>WH</b> - white
02	<b>GN</b> - green
...	<b>GR</b> - gray
24	<b>LG</b> - light gray
	<b>PG</b> - Phoenix Green
	<b>OR</b> - orange
	<b>BL</b> - blue
	<b>BK</b> - black



**Certification**



Pluggable Terminal Block /  
Pitch 5.00mm

Part No.: A14L046

Customer:

DRW:	Bill	CHKD	Lord	MATL:	Jimmy	TOLERANCE	Sam	DATE	14.3.2009
APPD:	Louis			FINISH	Georg			Sheet No.	2 from 3

[www.edcon-components.com](http://www.edcon-components.com)

email: [info@edcon-components.com](mailto:info@edcon-components.com)

# EDCON-COMPONENTS



## Soldering - Profil

### Classification Reflow Profile (JEDEC J-STD-020C)



Pluggable Terminal Block /  
Pitch 5.00mm

Part No.: A14L046

Customer:

DRW:	Bill	CHKD	Lord	MATL:	Jimmy	TOLERANCE	Sam	DATE	14.3.2009
APPD:	Louis			FINISH	Georg		Sheet No.	3 from 3	

[www.edcon-components.com](http://www.edcon-components.com)

email: [info@edcon-components.com](mailto:info@edcon-components.com)