


EDCON-COMPONENTS



Drawing



P.C.B. Layout

Specification

APPROVAL	ULus	CE
Electrical		
Standard	UL	IEC
Rated voltage	300V	320V
Rated current	15A	20A
Wire range	28-12 AWG	2.5mm ²
Withstanding voltage	AC 2500V/1min	
Mechanical		
Ambient temperature	-40°C ~ +105°C	
Strip length	7mm	
Screw, Torque	M2.5, 0.4Nm (3.5Lb-In.)	
Dimensions		
Pitch	5.08mm	
Poles	2P - 12P	
Material		
Housing	PA66 (UL94V-0)	
Contact	Phosphor Bronze	
Cage	Brass, Ni plated	
Terminal screw	steel, Cr ³⁺ Zn plated	



Certification



Pluggable Terminal Block /
Pitch 5.08mm

Part No.: A14M036

Customer:

DRW:	Bill	CHKD	Lord	MATL:	Jimmy	TOLERANCE	Sam	DATE	14.3.2009
APPD:	Louis			FINISH	Georg			Sheet No.	1 from 3

www.edcon-components.com

email: info@edcon-components.com

EDCON-COMPONENTS



Ordering Informations

Serie	-	No. of Pole	Body-Color	-	Customer Request
A14M036	-	XX	XX	-	X

XX = total	WH - white
02	GN - green
...	GR - gray
12	LG - light gray
	PG - Phoenix Green
	OR - orange
	BL - blue
	BK - black



Certification



Pluggable Terminal Block /
Pitch 5.08mm

Part No.: A14M036

Customer:

DRW:	Bill	CHKD	Lord	MATL:	Jimmy	TOLERANCE	Sam	DATE	14.3.2009
APPD:	Louis			FINISH	Georg			Sheet No.	2 from 3


www.edcon-components.com

email: info@edcon-components.com



Soldering - Profil

Classification Reflow Profile (JEDEC J-STD-020C)



Pluggable Terminal Block / Pitch 5.08mm	
Part No.:	A14M036
Customer:	

DRW:	Bill	CHKD	Lord	MATL:	Jimmy	TOLERANCE	Sam	DATE	14.3.2009
APPD:	Louis			FINISH	Georg		Sheet No.	3 from 3	