


Features

- Silicon Epitaxial Planar Diodes
- Electrical data identical with the device 1N4151
- Micro Melf package



Applications

- Extreme fast switches

Mechanical Data

- Case: MicroMELF Glass Case
- Weight: approx. 12.3 mg
- Cathode Band Color: Black

Absolute Maximum Ratings

($T_{amb}=25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Test Condition	Symbol	Value	Unit
Repetitive peak reverse voltage		V_{RRM}	75	V
Reverse voltage		V_R	50	V
Peak forward surge current	$t_p = 1 \text{ us}$	I_{FSM}	2	A
Repetitive peak forward current		I_{FRM}	450	mA
Forward current		I_F	200	mA
Average forward current	$V_R=0$	I_{FAV}	150	mA
Power dissipation		P_V	500	mW

Thermal Characteristics

($T_{amb}=25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Test Condition	Symbol	Value	Unit
Junction ambient	mounted on epoxy-glass hard tissue, Fig 4. 35 μm copper clad, 0.9 m^2 copper area per electrode	$R_{\theta JA}$	500	K/W
Junction temperature		T_J	175	$^{\circ}\text{C}$
Storage temperature range		T_{stg}	-65 to +175	$^{\circ}\text{C}$

Electrical Characteristics

($T_{amb}=25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Test Condition	Symbol	Min.	Typ.	Max.	Unit
Forward voltage	$I_F=50\text{mA}$	V_F		0.88	1.0	V
Reverse current	$V_R=50\text{V}$	I_R			50	nA
	$V_R=50\text{V}, T_J=150^{\circ}\text{C}$				50	μA
Breakdown voltage	$I_R=5\mu\text{A}, t_p/T=0.01, t_p=0.3\text{ms}$	$V_{(BR)}$	75			V
Diode capacitance	$V_R=0, f=1\text{MHz}, V_{RF}=50\text{mV}$	C_D			2	pF
Reverse recovery time	$I_F=I_R=10\text{mA}, i_R=1\text{mA}$	t_{rr}			4	ns
	$I_F=10\text{mA}, V_R=6\text{V}, i_R=0.1 \times I_R, R_L=100\Omega$				2	

Typical characteristics

($T_{amb}=25^{\circ}\text{C}$ unless otherwise specified)




Fig. 1 Reverse Current vs. Junction Temperature




Fig. 3 Diode Capacitance vs. Reverse Voltage




Fig. 2 Forward Current vs. Forward Voltage




Fig. 4 Board for $R_{th,JA}$ definition (in mm)

Package Dimensions in mm (inches)

