


Type Code


CPT44A12-1.1-W100:

Chinasound Piezo Transducer 44mm diameter, type A(=14mm height), 12Vp-p rated voltage – 1.1KHz resonant frequency – Wire length 100mm

Picture



Frequency Response Curve



Technical Terms

Type	CPT44A12-1.1-W100	
Rated Voltage (square wave)	(Vp-p)	12
Operating Voltage (square wave)	(Vp-p)	1~30
Rated Current at 12Vp-p, 1.1KHz	(mA)	3 max.
Capacitance at 100Hz, 1V	(pF)	70000±30%
SPL at 12Vp-p square wave, 10cm, 1.1KHz	(dB)	85 min.
Resonant Frequency	(Hz)	1100±500
Operating Temperature	(°C)	-20~+60
Storage Temperature	(°C)	-30~+70
Weight	(g)	10.0

Reliability

Life Test	Operate the part at 12Vp-p in room temperature continuously for 1000 hours.
Operating Temperature	Driving from -20 °C to +60 °C within 30 minutes for 2 cycles
High Temperature	+70 °C+/-2 °C, 120hrs
Low Temperature	-30 °C+/-2 °C, 120hrs
Humidity	+60 °C+/-2 °C, 90~95%RH, 120hrs
Thermal Shock	-30 °C+/-2 °C, 1hr→+20 °C,5min,→+70 °C+/-2 °C, 1hr→+20 °C,5min, 5 cycles
Shock	980/s ² (=100g) shock for each 3 mutually perpendicular directions to each of 3 times by half sine wave
Vibration	1.5mm with 10 to 50Hz of vibration frequency to each of 3 perpendicular direction for 2 hrs
Drop Test	Dropped naturally from 700mm height onto the surface of 10mm thick wooden board. 2 directions - upper and side of the part are to be applied.

All specifications must be satisfied after the test (Recovery:2 to 4 hrs of recovery under the standard condition after the removal from test chamber)

Dimensions (Unit:mm)

