

Type Code


CPT45A12-2.5:

Chinasound Piezo Transducer 45mm diameter; type A(=23.2mm height), 12Vp-p rated voltage – 2.5KHz resonant frequency

Picture



Frequency Response Curve



Technical Terms

Type	CPT45A12-2.5	
Rated Voltage (square wave)	(Vp-p)	12
Operating Voltage (square wave)	(Vp-p)	3~50
Rated Current at 12Vp-p, 2.5KHz	(mA)	20 max.
Capacitance at 100Hz, 1V	(pF)	250000±30%
SPL at 12Vp-p square wave, 100cm, 2.5KHz	(dB)	95 min.
Resonant Frequency	(Hz)	2500±500
Operating Temperature	(°C)	-30~+95
Storage Temperature	(°C)	-40~+105
Weight	(g)	11.0

Reliability

Life Test	Operate the part at 12Vp-p in room temperature continuously for 1000 hours.
Operating Temperature	Driving from -30 °C to +95 °C within 30 minutes for 2 cycles
High Temperature	+105 °C+/-2 °C, 120hrs
Low Temperature	-40 °C+/-2 °C, 120hrs
Humidity	+60 °C+/-2 °C, 90~95%RH, 120hrs
Thermal Shock	-40 °C+/-2 °C, 1hr→+20 °C,5min,→+105 °C+/-2 °C, 1hr→+20 °C,5min, 5 cycles
Shock	980m/s ² (=100g) shock for each 3 mutually perpendicular directions to each of 3 times by half sine wave
Vibration	1.5mm with 10 to 50Hz of vibration frequency to each of 3 perpendicular direction for 2 hrs
Drop Test	Dropped naturally from 700mm height onto the surface of 10mm thick wooden board. 2 directions - upper and side of the part are to be applied.

All specifications must be satisfied after the test (Recovery:2 to 4 hrs of recovery under the standard condition after the removal from test chamber)

Dimensions (Unit:mm)

