

**Type Code**


**CPT39YF09-3.2:**

Chinasound Piezo Transducer 39mm diameter; type Y (=16mm height, self driven type with Feedback Disc), 12VDC voltage – 3.2KHz resonant frequency

**Picture**



**Drive Circuit**



**Technical Terms**

Type	CPT39YF12-3.2	
Rated Voltage	(VDC)	12
Operating Voltage	(VDC)	6~20
Rated Current at 12VDC	(mA)	15 max.
Capacitance at 1KHz	(pF)	25000+/-30%
Sound Output at 12VDC 10cm	(dBA)	105 min.
Resonant Frequency	(Hz)	3200+/-500
Operating Temperature	(°C)	-20~+70
Storage Temperature	(°C)	-30~+80
Weight	(g)	9.1

**Reliability**

Life Test	Operate the part at 12VDC in room temperature continuously for 1000 hours.
Operating Temperature	Driving from -20 °C to +70 °C within 30 minutes for 2 cycles
High Temperature	+80 °C+/-2 °C, 120hrs
Low Temperature	-30 °C+/-2 °C, 120hrs
Humidity	+60 °C+/-2 °C, 90~95%RH, 120hrs
Thermal Shock	-30 °C+/-2 °C, 1hr→+20 °C,5min,→+80 °C+/-2 °C, 1hr→+20 °C,5min, 5 cycles
Shock	980m/s <sup>2</sup> (=100g) shock for each 3 mutually perpendicular directions to each of 3 times by half sine wave
Vibration	1.5mm with 10 to 50Hz of vibration frequency to each of 3 perpendicular direction for 2 hrs
Drop Test	Dropped naturally from 700mm height onto the surface of 10mm thick wooden board. 2 directions - upper and side of the part are to be applied.

All specifications must be satisfied after the test (Recovery: 2 to 4 hrs of recovery under the standard condition after the removal from test chamber)

**Dimensions (Unit:mm)**

