

Type Code


CPT39ZF09-3.4-S:

Chinasound Piezo Transducer 39mm diameter, type Z (=20mm height) self driven type with Feedback piezo disc, 9VDC voltage – 3.4KHz resonant frequency – Spring terminals

Picture



Drive Circuit



Characteristics at 30cm



Technical Terms

Type	CPT39ZF09-3.4-S	
Rated Voltage	(VDC)	9
Operating Voltage	(VDC)	6~13
Rated Current	(mA)	20 max. at 9VDC; 25 max. at 12VDC
Capacitance at 1KHz	(pF)	25000+-30%
Sound Output at 30cm	(dBA)	100 min. at 9VDC; 110 min. at 12VDC
Resonant Frequency	(Hz)	3400+-500
Operating Temperature	(°C)	-20~+70
Storage Temperature	(°C)	-30~+80
Weight	(g)	14

Reliability

Life Test	Operate the part at 9VDC in room temperature continuously for 1000 hours.
Operating Temperature	Driving from -20 °C to +70 °C within 30 minutes for 2 cycles
High Temperature	+80 °C+/-2 °C, 120hrs
Low Temperature	-30 °C+/-2 °C, 120hrs
Humidity	+60 °C+/-2 °C, 90~95%RH, 120hrs
Thermal Shock	-30 °C+/-2 °C, 1hr→+20 °C,5min,→+80 °C+/-2 °C, 1hr→+20 °C,5min, 5 cycles
Shock	980m/s ² (=100g) shock for each 3 mutually perpendicular directions to each of 3 times by half sine wave
Vibration	1.5mm with 10 to 50Hz of vibration frequency to each of 3 perpendicular direction for 2 hrs
Drop Test	Dropped naturally from 700mm height onto the surface of 10mm thick wooden board. 2 directions - upper and side of the part are to be applied.

All specifications must be satisfied after the test (Recovery:2 to 4 hrs of recovery under the standard condition after the removal from test chamber)

Dimensions (Unit:mm)

