



EDCON-COMPONENTS





Specifications

Voltage Rating:	600V AC/DC
Current Rating	9A AC/DC
Operating Temperature	.-25°C ~ +105°C
Contact Resistance	20 milli Ohm max.
Withstanding Voltage	1500V AC / minute
Insulation Resistance	1000Mega Ohm min
Material:	Nylon 66 UL94V-0
Color of body:	White

Drawing (dimensions all into mm)



PCb Layout



Wafer Serie T68R1014 Pitch
4,14mm

Part No.: **T68R1014-**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	13.04.2014
APPD:	Schumi			FINISH	Jamy		Sheet No.	1 from 3	Customer:

www.edcon-components.com

email: info@edcon-components.com

EDCON-COMPONENTS



Ordering Informations

Serie	Number of Pos.	Contact Plating	ROHS	Packing						
-------	----------------	-----------------	------	---------	--	--	--	--	--	--

T68R1014-	09	T	R	BU						
------------------	-----------	----------	----------	-----------	--	--	--	--	--	--

09 = Pos.	T= Tin Plated (Standard)	R= ROHS Conform	BU= Bulk (Standard)							
			TY= Tray Packing							
	G= Gold Flash Plated MOQ is important	N= NON ROHS Conform								

Wafer Serie T68R1014 Pitch 4,14mm

Part No.: **T68R1014-**


DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	13.04.2014
APPD:	Schumi			FINISH	Jamy		Sheet No.		2 from 3

Customer:



Soldering - Profile

Classification Reflow Profile (JEDEC J-STD-020C)



Wafer Serie T68R1014 Pitch 4,14mm	
Part No.:	T68R1014-

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	13.04.2014
APPD:	Schumi			FINISH	Jamy		Sheet No.	3 from 3	Customer: