



DATA SHEET

Uncoated Metallized Polyethelene Naphthalate Film Capacitor Stacked Type

Serie: I19009

Code / Range **104= 0,10 μ f**

Code / Volt **401= 400VDC**

Width **9,0 mm**

Height **8,1 mm**

Thickness **5,2 mm**

Pitch **7,5 mm**

Uncoated Metallized Polyethelene Naphthalate Film Capacitor Stacked Type	
Serie No.:	I19009

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	11.06.2011
APPD:	Schumi			FINISH	Jamy		Sheet No.		1 from 4

Customer:

EDCON-COMPONENTS



Features

- High pulse strength
- High reliability
- Operating temperature: -55°C ~ +150°C

Applications

Widely used in high-power CFL and electrical lighting (i.e, Automotive HID-Lamps)
DC impulse and pulse circuits (High temperature condition)

Specifications

Reference Standard	Q/ 052-2008				
Climatic Category	55/150/56				
Rated Temperature	125°C				
Operating Temperature Range	-55°C ~ +150°C (+125°C to +150°C ; decreasing factor 1,25% per °C for V _R (dc))				
Rated Voltage	250, 400, 630, 1000Volt				
Capacitance Range	0,0010 ~ 0,22µF				
Voltage Proof (Between Terminals)	1.40U _R (2s)				
Capacitance Tolerance	J=5% , K=10% , M=20%				
Dissipation Factor	≤ 0,0080 (20°C, 1KHz) ≤ 0,0150 (20°C, 10KHz)				
Insulation Resistance	≥ 10GΩ (20°C, 100V , 1min)				
Maximum Pulse Rise Time dV/dt (V/s)	UR /P(mm)	250V	400V	630V	1000V
	5,0	250	300	2000	3000
	7,5	200	275	1600	2000
	10,0	150	175	1000	1500

Dimensions



Case Dimension table

Case Code	W ±0,4 (mm)	H ±0,4 (mm)	T ±0,4 (mm)	P (mm)
A	9,0	8,1	5,2	7,5
C ±0,5 (mm)	Standard Length 18~22mm (Size by Size)			
Short Lead 4,5mm				

d ±0,05 (mm)

d= 0,6mm

**Uncoated Metallized
Polyethelene Naphthalate Film
Capacitor Stacked Type**

Part No.: **I19009**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	11.06.2011
APPD:	Schumi			FINISH	Jamy		Sheet No.		2 from 4

Customer:

EDCON-COMPONENTS



Ordering Informations

Serie	Range	Tolerance	Voltage	Case Code	Pitch Code	Lead Style	Lead Length (C)	ROHS	Packing Code	
-------	-------	-----------	---------	-----------	------------	------------	-----------------	------	--------------	--

I19009	104	M	401	A	3	N	LL	R	BU	
---------------	------------	----------	------------	----------	----------	----------	-----------	----------	-----------	--

104= 0,10µf	M= 20% Standard	401= 400VDC	A= look Case Dimension	3= 7,5mm	N= No function	LL= Long Lead (Standard)	R= ROHS Conform	BU= Bulk Ware
	K= 10%							
	J= 5%					IV= Individual Package		

Uncoated Metallized Polyethelene Naphthalate Film Capacitor Stacked Type

Part No.: **I19009**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	11.06.2011
APPD:	Schumi			FINISH	Jamy		Sheet No.		3 from 4

Customer:



Soldering Profile Curve

Classification Reflow Profile (JEDEC J-STD-020C)



**Uncoated Metallized
Polyethelene Naphthalate Film
Capacitor Stacked Type**
Part No.: **I19009**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	11.06.2011
APPD:	Schumi			FINISH	Jamy		Sheet No.	4 from 4	Customer: