



# DATA SHEET

**Metallized polypropylene film interference suppression capacitor Y2 Class**

**Serie: I24002**

Code / Range **153= 0,015 $\mu$ f**

Code / Volt **301= 300VAC**

Width **17,5 mm**

Height **11,0 mm**

Thickness **5,0 mm**

Pitch **15,0 mm**

**Metallized polypropylene film  
interference suppression  
capacitor Y2 Class**

Serie No.: **I24002**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	20.05.2011	Customer:
APPD:	Schumi			FINISH	Jamy		Sheet No.	1 from 4		

# EDCON-COMPONENTS



## Features

- Metallized polypropylene structure
- Withstanding overvoltage stressing
- Excellent active and passive flame resistant abilities
- Widely used in in line to ground, line-by-pass, antenna coupling interference suppression

## Dimensions

### Specifications

Climatic Category/ passive Flammability Class	40/110/56B	
Operating Temperature Range:	-40°C ~ +110°C	
Class	Y2	
Rated Voltage:	300VAC	
Maximum continuous AC voltage	480VAC	
Maximum continuous DC voltage	1250VDC	
Capacitance Range:	0,0010µF ~ 1,0µF	
Capacitance Tolerance:	± 10% (K), ± 20% (M)	
Voltage Proof	Between Terminals:	2000/3400 (Vacc) (2s)
	Between Terminals to Case:	2380 (Vac) (1min)
Insulation Resistance	≥15000MΩ, C <sub>R</sub> ≤0,33µF	( 20°C, 100V, 1min)
	≥5000s, C <sub>R</sub> ≤0,33µF	
Dissipation Factor	≤30x10 <sup>-4</sup> (1kHz,20°C)	≤40x10 <sup>-4</sup> (10kHz,20°C)



### Case Dimension table

Case Code	W ±0,4 (mm)	H ±0,4 (mm)	T ±0,4 (mm)	P (mm)
<b>A</b>	17,5	11,0	5,0	15,0

C ±0,5 (mm)

Standard Length 18~26mm (Size by Size)

Short Lead 4,5mm

d ±0,05 (mm)

d= 0,8mm

**Metallized polypropylene film  
interference suppression  
capacitor Y2 Class**

Part No.: **I24002**

  	IEC 60384-14:2005, Y2 250VAC; 0,001µF~1,0µF, 40/110/56B ( Certificate No.) CQC040001009958					
	EN 60384-14:2005 Y2 30VAC; 0,001µF~1,0µF, 40/110/56B ( Certificate No. ) SE/0366-2B Ref. No. 916516					
	UL1414, CSA C22.2 No.1, 250VAC, 0,0047µF to 1,0µF (Certificate No.) E186600					
	UL1283, CSA C22.2 No.8 300/480VAC, 0,010µF ~ 1,0µF ( Certificate No. ) E186662					
CB Test Certificate		IEC 60384-14:2005 Y2, 300VAC, 0,001µF ~ 1,0µF, 40/110/56B ( Certificate No. ): SE-60440				

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	20.05.2011	Customer:
APPD:	Schumi			FINISH	Jamy		Sheet No.	2 from 4		

[www.edcon-components.com](http://www.edcon-components.com)

email: [info@edcon-components.com](mailto:info@edcon-components.com)

# EDCON-COMPONENTS



## Ordering Informations

Serie	Range	Tolerance	Voltage	Case Code	Pitch Code	Lead Style	Lead Length C	ROHS	Packing Code	
-------	-------	-----------	---------	-----------	------------	------------	---------------	------	--------------	--

<b>I24002</b>	<b>153</b>	<b>M</b>	<b>301</b>	<b>A</b>	<b>6</b>	<b>N</b>	<b>LL</b>	<b>R</b>	<b>BU</b>	
---------------	------------	----------	------------	----------	----------	----------	-----------	----------	-----------	--

<b>153=</b> 0,015µf	<b>M=</b> 20% Standard <b>K=</b> 10%	<b>301=</b> 300VAC	<b>A=</b> look Case Dimension	<b>6=</b> 15,0mm	<b>N=</b> No function	<b>LL=</b> Long Lead (Standard) <b>45=</b> Lead Length 4,5mm	<b>R=</b> ROHS Conform <b>N=</b> NON ROHS Conform	<b>BU=</b> Bulk Ware <b>TB=</b> Tape Box <b>IV=</b> Individual Package
---------------------	--	--------------------	----------------------------------	------------------	--------------------------	---	---	---

**Metallized polypropylene film  
interference suppression  
capacitor Y2 Class**

Part No.: **I24002**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	20.05.2011
APPD:	Schumi			FINISH	Jamy		Sheet No.		3 from 4

Customer:



Soldering Profile Curve

Classification Reflow Profile (JEDEC J-STD-020C)



**Metallized polypropylene film  
interference suppression  
capacitor Y2 Class**

Part No.: **I24002**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	20.05.2011
APPD:	Schumi			FINISH	Jamy		Sheet No.	4 from 4	

Customer: