



# DATA SHEET

## Metallized polypropylene film capacitor (Box-Type)

### Serie: I37007

Code / Range **153= 0,015 $\mu$ f**

Code / Volt **202= 2000VDC**

Width **26,5 mm**

Height **15,0 mm**

Thickness **6,0 mm**

Pitch **22,5 mm**

Metallized polypropylene film  
capacitor (Box-Type)

Serie No.: **I37007**

Customer:

|       |        |      |        |        |        |           |           |          |            |
|-------|--------|------|--------|--------|--------|-----------|-----------|----------|------------|
| DRW:  | Jason  | CHKD | Wilson | MATL:  | Wilson | TOLERANCE | Mason     | DATE     | 14.05.2011 |
| APPD: | Schumi |      |        | FINISH | Jamy   |           | Sheet No. | 1 from 4 |            |

# EDCON-COMPONENTS



## Features

- Metallized Polypropylen structure
- Low Loss at high frequency
- Small inherent temperature rise
- Plastic case (UL94V-0), Epoxy resin sealing

## Dimensions

### Specifications

|                             |   |
|-----------------------------|---|
| Reference Standard          | GB/T 10190 (IEC 60384-16)   |
| Climatic Category           | 40/105/21   |
| Rated Temperature           | . +85°C   |
| Operating Temperature Range | . -40°C ~ +105°C  |
|                             | (+85°C to +105°C ; decreasing factor 1,25% per °C for V <sub>R</sub> (dc))  |
| Rated Voltage               | 160Vdc(90Vac); 250Vdc(160Vac);<br>400Vdc(220Vac); 630Vdc(250Vac);<br>1000Vdc(400Vac); 1600Vdc(600Vac);<br>2000Vdc(700Vac) |
| Capacitance Range           | 0,00056µF ~ 15,0µF  |
| Capacitance Tolerance       | J=5% , K=10%, N=15%   |
| Voltage Proof               | 2000VAC ( 60s)  |
| Dissipation Factor          | ≤ 0,0020 ( 1KHz, 20°C)  |
| Insulation Resistance       | ≥ 3000s (20°C, 100V, 1Min)  |
| Pitch Width                 | from 5,0mm ~ 27,5mm   |



Case Dimension table

| Case Code | W ±0,4 (mm) | H ±0,4 (mm) | T ±0,4 (mm) | P (mm) |
|-----------|-------------|-------------|-------------|--------|
| <b>A</b>  | 26,5        | 15,0        | 6,0         | 22,5   |

C ±0,5 (mm)

Standard Length 18~26mm (Size by Size)

Short Lead 4,5mm

d ±0,05 (mm)

d= 0,8mm

**Metallized polypropylene film capacitor (Box-Type)**

Part No.: **I37007**

|       |        |      |        |        |        |           |           |          |            |           |
|-------|--------|------|--------|--------|--------|-----------|-----------|----------|------------|-----------|
| DRW:  | Jason  | CHKD | Wilson | MATL:  | Wilson | TOLERANCE | Mason     | DATE     | 14.05.2011 | Customer: |
| APPD: | Schumi |      |        | FINISH | Jamy   |           | Sheet No. | 2 from 4 |            |           |

# EDCON-COMPONENTS



## Ordering Informations

| Serie | Range | Tolerance | Voltage | Case Code | Pitch Code | Lead Style | Lead Length C | ROHS | Packing Code |  |
|-------|-------|-----------|---------|-----------|------------|------------|---------------|------|--------------|--|
|-------|-------|-----------|---------|-----------|------------|------------|---------------|------|--------------|--|

|               |            |          |            |          |          |          |           |          |           |  |
|---------------|------------|----------|------------|----------|----------|----------|-----------|----------|-----------|--|
| <b>I37007</b> | <b>153</b> | <b>M</b> | <b>202</b> | <b>A</b> | <b>9</b> | <b>N</b> | <b>LL</b> | <b>R</b> | <b>BU</b> |  |
|---------------|------------|----------|------------|----------|----------|----------|-----------|----------|-----------|--|

|              |                 |              |                        |           |                |   |  |   |
|--------------|-----------------|--------------|------------------------|-----------|----------------|---|--|---|
| 153= 0,015µf | M= 20% Standard | 202= 2000VDC | A= look Case Dimension | 9= 22,5mm | N= No function | LL= Long Lead (Standard)<br>45= Lead Length 4,5mm | R= ROHS Conform<br>N= NON ROHS Conform | BU= Bulk Ware<br>TB= Tape Box<br>IV= Individual Package |
|              | K= 10%          |              |                        |           |                |   |  |   |
|              | J= 5%           |              |                        |           |                |   |  |   |
|              | H= 3%           |              |                        |           |                |   |  |   |
|              | G= 2%           |              |                        |           |                |   |  |   |

**Metallized polypropylene film capacitor (Box-Type)**

Part No.: **I37007**

|       |        |      |        |        |        |           |           |          |            |
|-------|--------|------|--------|--------|--------|-----------|-----------|----------|------------|
| DRW:  | Jason  | CHKD | Wilson | MATL:  | Wilson | TOLERANCE | Mason     | DATE     | 14.05.2011 |
| APPD: | Schumi |      |        | FINISH | Jamy   |           | Sheet No. | 3 from 4 |            |

Customer:



Soldering Profile Curve

Classification Reflow Profile (JEDEC J-STD-020C)



|   |               |
|---|---------------|
| <b>Metallized polypropylene film capacitor (Box-Type)</b> |               |
| Part No.:   | <b>I37007</b> |
| Customer:   |               |

|       |        |      |        |        |        |           |           |          |            |
|-------|--------|------|--------|--------|--------|-----------|-----------|----------|------------|
| DRW:  | Jason  | CHKD | Wilson | MATL:  | Wilson | TOLERANCE | Mason     | DATE     | 14.05.2011 |
| APPD: | Schumi |      |        | FINISH | Jamy   |           | Sheet No. | 4 from 4 |            |