



DATA SHEET

Metallized polypropylene film capacitor Box-Type

Serie: I40002

Code / Range **362= 0,0036µf**

Code / Volt **501= 500VAC**

Width **17,5 mm**

Height **11,0 mm**

Thickness **5,0 mm**

Pitch **15,0 mm**

**Metallized polypropylene film
capacitor Box-Type**

Serie No.: **I40002**

| | | | | | | | | | | |
|-------|--------|------|--------|--------|--------|-----------|-----------|----------|------------|-----------|
| DRW: | Jason | CHKD | Wilson | MATL: | Wilson | TOLERANCE | Mason | DATE | 21.05.2011 | Customer: |
| APPD: | Schumi | | | FINISH | Jamy | | Sheet No. | 1 from 4 | | |

EDCON-COMPONENTS



Features

Low Cost at high frequency

Small inherent temperature rise, high temperature range

Plastic case (UL94V-0) Epoxy resin sealing

Dimensions

Applications

Pulse applications with high A.C. voltage and high current

Electrical lighting (i.e. Electric ballast, E-HID)

High frequency A.C.loads

Specifications

| | |
|-----------------------------------|---|
| Referance Standard | GB/T 14579 (IEC 60384-17) |
| Climatic Category | 55/125/56 |
| Rated Temperature | . +85°C |
| Operating Temperature Range | . -55°C ~ +125°C |
| | (+85°C to +125°C ; decreasing factor 1,25% per °C for V _R (dc) |
| Voltage Proof (Between Terminals) | 1.60U _R (5s) |
| Capacitance Tolerance | H=3% , J=5%, K=10% |
| Disspation Factor | ≤ 0,0010 (1KHz, 20°C) |
| Insulation Resistance | ≥75 * 10 ³ MΩ (20°C, 100V ,1min) |
| Pitch Width | from 7,5mm ~ 22,5mm |

| Rated Voltage | 400VAC | | 500VAC | | 600VAC | | 700VAC | | 900VAC | |
|---------------|--------|------|--------|------|--------|-------|--------|-------|--------|-------|
| Pitch (mm) | 7,5 | ≥7,5 | 7,5 | ≥7,5 | ≤10,0 | ≥10,0 | 10 | ≥10,0 | 15 | ≥15,0 |
| VDC © | 1000 | 1300 | 1300 | 1400 | 1400 | 1600 | 1600 | 2000 | 2500 | |



Case Dimension table

| Case Code | W ±0,4 (mm) | H ±0,4 (mm) | T ±0,4 (mm) | P (mm) |
|-----------|-------------|-------------|-------------|--------|
| A | 17,5 | 11,0 | 5,0 | 15,0 |

C ±0,5 (mm)

Standard Length 18~26mm (Size by Size)

Short Lead 4,5mm

d ±0,05 (mm)

d= 0,8mm

Metallized polypropylene film capacitor Box-Type

Part No.: **I4002**

| | | | | | | | | | | |
|-------|--------|------|--------|--------|--------|-----------|-----------|----------|------------|-----------|
| DRW: | Jason | CHKD | Wilson | MATL: | Wilson | TOLERANCE | Mason | DATE | 21.05.2011 | Customer: |
| APPD: | Schumi | | | FINISH | Jamy | | Sheet No. | 2 from 4 | | |

www.edcon-components.com

email: info@edcon-components.com

EDCON-COMPONENTS



Ordering Informations

| Serie | Range | Tolerance | Voltage | Case Code | Pitch Code | Lead Style | Lead Length C | ROHS | Packing Code | |
|-------|-------|-----------|---------|-----------|------------|------------|---------------|------|--------------|--|
|-------|-------|-----------|---------|-----------|------------|------------|---------------|------|--------------|--|

| | | | | | | | | | | |
|---------------|------------|----------|------------|----------|----------|----------|-----------|----------|-----------|--|
| I40002 | 362 | K | 501 | A | 6 | N | LL | R | BU | |
|---------------|------------|----------|------------|----------|----------|----------|-----------|----------|-----------|--|

| | | | | | | | | |
|-------------------------|---|-----------------------|----------------------------------|------------------|--------------------------|---|---|---|
| 362= 0,0036µf | K= 10% Standard J= 5% H= 3% | 501= 500VAC | A= look Case Dimension | 6= 15,0mm | N= No function | LL= Long Lead (Standard) 45= Lead Length 4,5mm | R= ROHS Conform N= NON ROHS Conform | BU= Bulk Ware TB= Tape Box IV= Individual Package |
|-------------------------|---|-----------------------|----------------------------------|------------------|--------------------------|---|---|---|

**Metallized polypropylene film
capacitor Box-Type**

Part No.: **I40002**

Customer:

| | | | | | | | | | |
|-------|--------|------|--------|--------|--------|-----------|-----------|------|------------|
| DRW: | Jason | CHKD | Wilson | MATL: | Wilson | TOLERANCE | Mason | DATE | 21.05.2011 |
| APPD: | Schumi | | | FINISH | Jamy | | Sheet No. | | 3 from 4 |



Soldering Profile Curve

Classification Reflow Profile (JEDEC J-STD-020C)



| | |
|---|---------------|
| Metallized polypropylene film capacitor Box-Type | |
| Part No.: | I40002 |
| Customer: | |

| | | | | | | | | | |
|-------|--------|------|--------|--------|--------|-----------|-----------|----------|------------|
| DRW: | Jason | CHKD | Wilson | MATL: | Wilson | TOLERANCE | Mason | DATE | 21.05.2011 |
| APPD: | Schumi | | | FINISH | Jamy | | Sheet No. | 4 from 4 | |