



# DATA SHEET

## Metallized polypropylene film capacitor Box-Type

### Serie: I40002

Code / Range **223= 0,022µf**

Code / Volt **501= 500VAC**

Width **26,5 mm**

Height **15,0 mm**

Thickness **6,0 mm**

Pitch **22,5 mm**

**Metallized polypropylene film  
capacitor Box-Type**

Serie No.: **I40002**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	21.05.2011	Customer:
APPD:	Schumi			FINISH	Jamy		Sheet No.	1 from 4		

# EDCON-COMPONENTS



## Features

Low Cost at high frequency

Small inherent temperature rise, high temperature range

Plastic case (UL94V-0) Epoxy resin sealing

## Dimensions

## Applications

Pulse applications with high A.C. voltage and high current

Electrical lighting (i.e. Electric ballast, E-HID)

High frequency A.C.loads

## Specifications

Referance Standard	GB/T 14579 (IEC 60384-17)
Climatic Category	55/125/56
Rated Temperature	. +85°C
Operating Temperature Range	. -55°C ~ +125°C
	(+85°C to +125°C ; decreasing factor 1,25% per °C for V <sub>R</sub> (dc)
Voltage Proof (Between Terminals)	1.60U <sub>R</sub> (5s)
Capacitance Tolerance	H=3% , J=5%, K=10%
Disspation Factor	≤ 0,0010 (1KHz, 20°C)
Insulation Resistance	≥75 * 10 <sup>3</sup> MΩ (20°C, 100V ,1min)
Pitch Width	from 7,5mm ~ 22,5mm

Rated Voltage	400VAC		500VAC		600VAC		700VAC		900VAC	
Pitch (mm)	7,5	≥7,5	7,5	≥7,5	≤10,0	≥10,0	10	≥10,0	15	≥15,0
VDC ©	1000	1300	1300	1400	1400	1600	1600	2000	2500	



## Case Dimension table

Case Code	W ±0,4 (mm)	H ±0,4 (mm)	T ±0,4 (mm)	P (mm)
<b>A</b>	26,5	15,0	6,0	22,5

C ±0,5 (mm)

Standard Length 18~26mm (Size by Size)

Short Lead 4,5mm

d ±0,05 (mm)

d= 0,8mm

**Metallized polypropylene film capacitor Box-Type**

Part No.: **I4002**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	21.05.2011	Customer:
APPD:	Schumi			FINISH	Jamy		Sheet No.	2 from 4		

[www.edcon-components.com](http://www.edcon-components.com)

email: info@edcon-components.com

# EDCON-COMPONENTS



## Ordering Informations

Serie	Range	Tolerance	Voltage	Case Code	Pitch Code	Lead Style	Lead Length C	ROHS	Packing Code	
-------	-------	-----------	---------	-----------	------------	------------	---------------	------	--------------	--

<b>I40002</b>	-	<b>223</b>	<b>K</b>	<b>501</b>	<b>A</b>	<b>9</b>	<b>N</b>	<b>LL</b>	<b>R</b>	<b>BU</b>
---------------	---	------------	----------	------------	----------	----------	----------	-----------	----------	-----------

<b>223</b> = 0,022µf	<b>K</b> = 10% Standard	<b>501</b> = 500VAC	<b>A</b> = look Case Dimension	<b>9</b> = 22,5mm	<b>N</b> = No function	<b>LL</b> = Long Lead (Standard)	<b>R</b> = ROHS Conform	<b>BU</b> = Bulk Ware
	<b>J</b> = 5%					<b>45</b> = Lead Length 4,5mm	<b>N</b> = NON ROHS Conform	<b>TB</b> = Tape Box
	<b>H</b> = 3%							<b>IV</b> = Individual Package

**Metallized polypropylene film  
capacitor Box-Type**

Part No.: **I40002**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	21.05.2011
APPD:	Schumi			FINISH	Jamy		Sheet No.		3 from 4

Customer:



Soldering Profile Curve

Classification Reflow Profile (JEDEC J-STD-020C)



<b>Metallized polypropylene film capacitor Box-Type</b>	
Part No.:	<b>I40002</b>
Customer:	

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	21.05.2011
APPD:	Schumi			FINISH	Jamy		Sheet No.	4 from 4	