



# DATA SHEET

## Metallized polypropylene film capacitor Box-Type

### Serie: I40003

Code / Range **273= 0,027µf**

Code / Volt **601= 600VAC**

Width **17,5 mm**

Height **16,0 mm**

Thickness **10,0 mm**

Pitch **15,0 mm**

**Metallized polypropylene film  
capacitor Box-Type**

Serie No.: **I40003**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	21.05.2011	Customer:
APPD:	Schumi			FINISH	Jamy		Sheet No.	1 from 4		

# EDCON-COMPONENTS



## Features

Low Cost at high frequency

Small inherent temperature rise, high temperature range

Plastic case (UL94V-0) Epoxy resin sealing

## Dimensions

## Applications

Pulse applications with high A.C. voltage and high current

Electrical lighting (i.e. Electric ballast, E-HID)

High frequency A.C.loads

## Specifications

Referance Standard	GB/T 14579 (IEC 60384-17)	
Climatic Category	55/125/56	
Rated Temperature	+85°C	
Operating Temperature Range	-55°C ~ +125°C	
	(+85°C to +125°C ; decreasing factor 1,25% per °C for V <sub>R</sub> (dc)	
Voltage Proof (Between Terminals)	1.60U <sub>R</sub> (5s)	
Capacitance Tolerance	H=3% , J=5%, K=10%	
Disspation Factor	≤ 0,0010 (1KHz, 20°C)	
Insulation Resistance	≥75 * 10 <sup>3</sup> MΩ (20°C, 100V ,1min)	
Pitch Width	from 7,5mm ~ 22,5mm	

Rated Voltage	400VAC		500VAC		600VAC		700VAC		900VAC	
Pitch (mm)	7,5	≥7,5	7,5	≥7,5	≤10,0	≥10,0	10	≥10,0	15	≥15,0
VDC ©	1000	1300	1300	1400	1400	1600	1600	2000	2500	



## Case Dimension table

Case Code	W ±0,4 (mm)	H ±0,4 (mm)	T ±0,4 (mm)	P (mm)
<b>A</b>	17,5	16,0	10,0	15,0

C ±0,5 (mm)

Standard Length 18~26mm (Size by Size)

Short Lead 4,5mm

d ±0,05 (mm)

d= 0,8mm

**Metallized polypropylene film capacitor Box-Type**

Part No.: **I4003**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	21.05.2011	Customer:
APPD:	Schumi			FINISH	Jamy		Sheet No.	2 from 4		

[www.edcon-components.com](http://www.edcon-components.com)

email: info@edcon-components.com

# EDCON-COMPONENTS



## Ordering Informations

Serie	Range	Tolerance	Voltage	Case Code	Pitch Code	Lead Style	Lead Length C	ROHS	Packing Code	
-------	-------	-----------	---------	-----------	------------	------------	---------------	------	--------------	--

<b>I40003</b>	-	<b>273</b>	<b>K</b>	<b>601</b>	<b>A</b>	<b>6</b>	<b>N</b>	<b>LL</b>	<b>R</b>	<b>BU</b>
---------------	---	------------	----------	------------	----------	----------	----------	-----------	----------	-----------

<b>273</b> = 0,027µf	<b>K</b> = 10% Standard	<b>601</b> = 600VAC	<b>A</b> = look Case Dimension	<b>6</b> = 15,0mm	<b>N</b> = No function	<b>LL</b> = Long Lead (Standard)	<b>R</b> = ROHS Conform	<b>BU</b> = Bulk Ware
	<b>J</b> = 5%					<b>45</b> = Lead Length 4,5mm	<b>N</b> = NON ROHS Conform	<b>TB</b> = Tape Box
	<b>H</b> = 3%							<b>IV</b> = Individual Package

**Metallized polypropylene film capacitor Box-Type**

Part No.: **I40003**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	21.05.2011
APPD:	Schumi			FINISH	Jamy		Sheet No.	3 from 4	

Customer:

email: [info@edcon-components.com](mailto:info@edcon-components.com)



Soldering Profile Curve

Classification Reflow Profile (JEDEC J-STD-020C)



<b>Metallized polypropylene film capacitor Box-Type</b>	
Part No.:	<b>I40003</b>
Customer:	

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	21.05.2011
APPD:	Schumi			FINISH	Jamy		Sheet No.	4 from 4	