

EDCON-COMPONENTS



Technical Discription

Drawing (Dimension in mm)

Electrical

Rated Voltage	250Volt (AC)
Rated Current	16A
Wire Range	1,0 ~ 2,5mm ²
Contact Resistance	20m Ω
Withstanding Voltage	1,6KV
Insulation Resistance	5000MmΩ / 1000V

Mechanical

Operating Temperature	-40°C ~ +105°C
Wire Strip Length	6-7mm
Screw Torque	3,5
Screw Size	M2,5

Dimensions

Pitch	10mm
Poles	3 Pos.

Materials

Housing	PA66, UL94V-0
Pin	Brass Tin Plated
Screw	Fe Ni-plated

**Pluggable Motor Terminal
Block 5Pos.**

Part No.: **A35017**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	22.09.2012	Customer:
APPD:	Schumi			FINISH	Jamy		Sheet No.	1 from 3		

EDCON-COMPONENTS



**Pluggable Motor Terminal
Block 5Pos.**

Part No.: **A35017**

Customer:


DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	22.09.2012
APPD:	Schumi			FINISH	Jamy		Sheet No.	2 from 3	



Ordering Informations

Serie	No. of Pos.	Body Color	Screw Type	ROHS	Packing	EDCON Cust. No.	Customer Version			
-------	-------------	------------	------------	------	---------	-----------------	------------------	--	--	--

A35017	05	BK	A	R	BU	xxxxxx	xxx			
---------------	-----------	-----------	----------	----------	-----------	---------------	------------	--	--	--

05= Number of Pos.		A= Slotted Screw Type (Standard) 	R= ROHS Conform N= NON ROHS Conform	BU= Bulk-Ware IV= Individual Package	xxxxxx= Customer Number	xxx= Customer Version ??(Printing)
	BK= Black					

Pluggable Motor Terminal Block 5Pos.
Part No.: A35017
Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	22.09.2012
APPD:	Schumi			FINISH	Jamy		Sheet No.		3 from 3