


# EDCON-COMPONENTS




## SPECIFICATION:

Current Rating: 50mA / 12VDC  
 Insulator Resistance: 100M Ohm 10VDC  
 Dielectric Withstanding: 250VAC for 1 mi.  
 Operating Temperature: -30°C ~ +85°C  
 Contact Resistance: 100m Ohm max.  
 Travel: 0,20 / +/-0,1mm

## Drawing



## P.C.B Layout



**Tact Switch 4,70 x 4,50mm**

Part No.: **Q12011**

Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	02.02.2008
APPD:	Schumi			FINISH	Jamy		Sheet No.	1 from 3	

# EDCON-COMPONENTS



## Ordering Informations

Serie	Total height w. Body	Fill with 0	Operating Force	Polarisation Peg	Electrical life	Fill with 0	ROHS	Packing		
<b>Q12011</b>	<b>045</b>	<b>X</b>	<b>181</b>	<b>Y</b>	<b>104</b>	<b>X</b>	<b>R</b>	<b>TRxxx</b>		

**045**= 4,5mm

<b>181</b> = 180gr	<b>Y</b> = with Peg	<b>104</b> = 100000 Cycles
<b>251</b> = 250gr		

<b>N</b> = non ROHS	<b>BU</b> = Bulk Ware
<b>R</b> = ROHS conform	<b>TY</b> = Tray Packing
	<b>TR102</b> = Tape/Reel Packing 1000PCS

**Tact Switch 4,70 x 4,50mm**


Part No.: **Q12011**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	02.02.2008
APPD:	Schumi			FINISH	Jamy		Sheet No.		2 from 3


Customer:



## Soldering Profile for Lead Soldering



## Soldering Profile for Lead Free Soldering



**Tact Switch 4,70 x 4,50mm**

Part No.: **Q12011**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	02.02.2008
APPD:	Schumi			FINISH	Jamy		Sheet No.	3 from 3	Customer:

[www.edcon-components.com](http://www.edcon-components.com)

email: [info@edcon-components.com](mailto:info@edcon-components.com)