





EDCON-COMPONENTS



Specifications

Current Rating:	3,0A
Insulation Resistance:	1000M Ohm min.
Contact Resistance:	20milli Ohm max.
Dielectric Voltage:	1000V AC for one minute
Operating Temperature:	-40°C ~ to +105°C
Insulator Material:	PBT/PA6T+30% G.F.(UL94V-0)
Contact Pin:	Brass
Contact Plating:	Gold Flash all over
No Side Slot A and B from 6 to 16Pin	
No Side Slot A from 18 to 58Pin	

PCB Layout



**Box Header Pitch
2,54x2,54mm**

Part No.: **T14A002**


Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	10.04.2009
APPD:	Schumi			FINISH	Jamy		Sheet No.		1 from 4

www.edcon-components.com

email: info@edcon-components.com

EDCON-COMPONENTS



Pin Code length table free configuration

Dimension (mm)				
	A			
A01	3,80			
A02	3,30			
A03	3,00			
A04				
A05				
A06				
A07				
A08				
A09				
A10				
A11				
A12				
A13				
A14				
A15				
A16				
A17				
A18				
A19				
A20				
A21				
A22				

Dimension (mm)				
	A			
A23				
A24				
A25				
A26				
A27				
A28				
A29				
A30				
A31				
A32				
A33				
A34				
A35				
A36				
A37				
A38				
A39				
A40				
A41				
A42				
A43				
A44				

Dimension (mm)				
	A			
A45				
A46				
A47				
A48				
A49				
A50				
A51				
A52				
A53				
A54				
A55				
A56				
A57				
A58				
A59				
A60				
A61				
A62				
A63				
A64				
A65				
A66				


**Box Header Pitch
2,54x2,54mm**

Part No.: **T14A002**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	10.04.2009
APPD:	Schumi			FINISH	Jamy		Sheet No.	2 from 4	

Customer:

EDCON-COMPONENTS



Ordering Informations

Serie	No. of Pos.	Contact Plating	Material	Color of Body	Pin Length Configuration	Option Latches	ROHS	Packing		
T14A002	XX	G0	PB	BK	A01	S	R	BU		


XX= 6, 8, 10, 12, 14, 16, 18, 20, 24, 26, 30, 34, 40, 44, 50, 56, 60, 64	G0= Gold Flash	PB= PBT PA= PA6T +30% GF f. ROHS	BK= Black	Axx = Look Table	S= Short Latches	N=NO ROHS conform	BU= Bulk Ware
	T0= Tin plated		BL= Blue		L= Long Latches		R=ROHS conform
	GA= 3μ Gold Plating		GR= Gray (427°C)		N= without Latches	TY= Tray	
	GB= 5μ Gold Plating	EG= Gray (413°C)					
	GC= 10μ Gold Plating						
	GD= 30μ Gold Plating						
	S0= Selectiv Plating Gold Flash / Tin						
	SD= Selectiv Tin/ 5μGold						
	SD= Selectiv Tin/ 10μ Gold Flash						
	SD= Selectiv Tin/ 20μ Gold	SD= Selectiv Tin/ 30μ Gold					

**Box Header Pitch
2,54x2,54mm**


Part No.: **T14A002**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	10.04.2009
APPD:	Schumi			FINISH	Jamy		Sheet No.		3 from 4


Customer:



Soldering Profile for Lead Soldering (P.B.T.)



Soldering Profile for Lead Free Soldering (Nylon 6T)



**Box Header Pitch
2,54x2,54mm**

Part No.: **T14A002**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	10.04.2009
APPD:	Schumi			FINISH	Jamy		Sheet No.	4 from 4	

Customer: