




Material



Material: PA6,
 Seal: Sealing Elastomers
 Protection Degree: Using suitable O-Sealing within clamping range ist protection degree can reach IP68
 Temperature Range: Stat. Min. -40°C max 100°C Short-term 120°C
 Note: According to the special needs of thread, V0 level joint product

Technical Drawing



**Multi Plastic Cable Gland
M Thread; Standard Long
Thread**

Part No.: **231028**

Customer:

DRW:	Jason	CHKD	Jules	MATL:	Wu	DATE	26.10.2021
APPD:	Join			FINISH	Shieh	Sheet	1 from 2

Copyright by S.Tiede



Dimension Table

Size	Thread	Clamping	Thread	Thread	Wrench	Packing
	Dimension	Range (mm)	AG (mm)	Length (mm)	Size (mm)	units
M16A	M16	2x3	16	8	19	100
M16B	M16	4x1,4	16	8	19	100
M18A	M18	2x3	18	8	22	100
M18B	M18	2x4	18	8	22	100
M18C	M18	3x3	18	8	22	100
M20A	M20	2x5	20	9	24	100
M20B	M20	3x2	20	9	24	100
M20C	M20	3x4	20	9	24	100
M20D	M20	6x3	20	9	24	100
M20E	M20	3x5	20	9	24	100
M24A	M24	2x6	24	10	27	50
M24B	M24	3x3	24	10	27	50
M24C	M24	3x4	24	10	27	50
M24D	M24	3x5,6	24	10	27	50
M24E	M24	4x4	24	10	27	50
M24F	M24	5x4	24	10	27	50
M24G	M24	6x4	24	10	27	50
M25A	M25	2x8	25	11	33	50
M25B	M25	3x7	25	11	33	50
M25C	M25	4x6	25	11	33	50
M25D	M25	2x6	25	11	33	50
M32A	M32	4x9	32	11	42	25
M32B	M32	6x6,5	32	11	42	25
M40A	M40	2x15	40	13	52	10
M40B	M40	5x9	40	13	52	10
M40C	M40	6x8	40	13	52	10
M40D	M40	7x9	40	13	52	10
M63A	M63	3x18	63	15	65	5
M63B	M63	6x12	63	15	65	5
M63C	M63	8x10	63	15	65	5

Ordering Information

Serie	Size	Color	ROHS	Packing	
-------	------	-------	------	---------	--

231028	-	M16A	7035	R	BU
--------	---	------	------	---	----

Look dimension table	7035= Gray RAL7035	R= ROHS Conform	BU= Poly Bag
	9005= Black RAL 9005	0= NON ROHS	
	9003= White RAL 9003		

**Multi Plastic Cable Gland
M Thread; Standard Long
Thread**

Part No.: **231028**
Customer:

DRW:	Jason	CHKD	Jules	MATL:	Wu	DATE	26.10.2021
APPD:	Join			FINISH	Shieh	Sheet	2 from 2

Copyright by S.Tiede