

EDCON-COMPONENTS



Technical Discription

Temperature Range: ABS= -40°C ~ +85°C
PC= -40°C ~ +120°C
Protection Degree IP66-67

Since a rrof on the top/bottem of the base is producted, the EDCON box is designed to be able to completely prevent rain or dust from penetrating.

A hinge is attached to the product as a hinge unit and the major partsd of draw latch are made of stainless to be aolid.

Hinge connection pins and draw latch are made of stainless and plastic to prevent rust.



Dimension (mm)											
W1	W3	H1	H3	H4	D1	D2	D3	M1	M2		
135	105	150	119,3	110	60	20	67,5	101	126		

**Sealed Plastic Enclosure
135 x 155 x 85mm**

Part No.: **H26009**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	12.02.2010
APPD:	Schumi			FINISH	Jamy		Sheet No.		1 from 4


Customer:
email: info@edcon-components.com

www.edcon-components.com

EDCON-COMPONENTS



Technical Drawing



**Sealed Plastic Enclosure
135 x 155 x 85mm**

Part No.: **H26009**

Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	12.02.2010
APPD:	Schumi			FINISH	Jamy		Sheet No.	2 from 4	

www.edcon-components.com

email: info@edcon-components.com



Accessories for Enclosures H260xx Serie

Ordering Informations

Serie	Material Base	Material Cover	Color Base	Color Cover	ROHS	Packing				
-------	---------------	----------------	------------	-------------	------	---------	--	--	--	--

H26009	A	A	G	G	R	S				
---------------	----------	----------	----------	----------	----------	----------	--	--	--	--

A= ABS	A= ABS	G= Gray	G= Gray	R= ROHS Conform	S= Standard Packing
P= Polycar - bonat	P= Polycar - bonat	T= Transparent	T= Transparent	N= NON ROHS Conform	I= Individual Packing

**Sealed Plastic Enclosure
135 x 155 x 85mm**

Part No.: **H26009**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	12.02.2010
APPD:	Schumi			FINISH	Jamy		Sheet No.		4 from 4

Customer: