

EDCON-COMPONENTS



Technical Discription

Temperature Range: ABS= -40°C ~ +85°C
PC= -40°C ~ +120°C
Protection Degree IP66-67

Since a roof on the top/bottom of the base is producted, the EDCON box is designed to be able to completely prevent rain or dust from penetrating.

A hinge is attached to the product as a hinge unit and the major partsd of draw latch are made of stainless to be aolid.

Hinge connection pins and draw latch are made of stainless and plastic to prevent rust.



Dimension (mm)												
W1	W3	H1	H3	H4	D1	D2	D3	M1	M2			
350	300	457,4	400	365	130	30	138	305	406			

**Sealed Plastic Enclosure
350 x 450 x 160mm**

Part No.: **H26038**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	12.02.2010	Customer:
APPD:	Schumi			FINISH	Jamy		Sheet No.	1 from 4		

www.edcon-components.com

Copyright by EDCON-COMPONENTS H.Schmitt

email: info@edcon-components.com

EDCON-COMPONENTS



Technical Drawing



**Sealed Plastic Enclosure
350 x 450 x 160mm**

Part No.: **H26038**

Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	12.02.2010
APPD:	Schumi			FINISH	Jamy		Sheet No.	2 from 4	

www.edcon-components.com

email: info@edcon-components.com



Accessories for Enclosures H260xx Serie

Ordering Informations

Serie	Material Base	Material Cover	Color Base	Color Cover	ROHS	Packing				
-------	---------------	----------------	------------	-------------	------	---------	--	--	--	--

H26038	A	A	G	G	R	S				
---------------	----------	----------	----------	----------	----------	----------	--	--	--	--

A= ABS	A= ABS	G= Gray	G= Gray	R= ROHS Conform	S= Standard Packing
P= Polycar - bonat	P= Polycar - bonat	T= Transparent	T= Transparent	N= NON ROHS Conform	I= Individual Packing

**Sealed Plastic Enclosure
350 x 450 x 160mm**

Part No.: **H26038**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	12.02.2010
APPD:	Schumi			FINISH	Jamy		Sheet No.	4 from 4	

Customer: