



EDCON-COMPONENTS





Specifications

Current Rating:	1,5 Ampere
Insulator Resistance:	5000 Megaohm min.
Contact Resistance:	20m Ohm max.
Dielectric Withstanding:	AC 500V
Operating Temperature:	.-65°C to +125°C
Contact Material:	Brass
Insulator Material:	PBT, UL 94V-0 Black
Contact Plating:	Tin, Gold or Selective Plated
Standard:	Gold Flash Overall

P.C.B Layout




Drawing




						Unless: Otherwise specified tolerance (mm)				Female Header Pitch 2,00mm	
						X	XX	XXX	XXXX		
DRW:	Jason	CHKD	Wilson	MATL:	Wilson	± 0,35	± 0,25	±0,20	±0,15	Customer:	
APPD:	Schumi			FINISH	Jamy	TOLERANCE	Mason	DATE	03.10.2018		
						Sheet No.			1 from 4		

EDCON-COMPONENTS



Pin Code length table free configuration


Order Code	Dimension (mm)			
	A			
A01	4,60			
A02				
A03				
A04				
A05				
A06				
A07				
A08				
A09				
A10				
A11				
A12				
A13				
A14				
A15				
A16				
A17				
A18				
A19				
A20				
A21				
A22				



Female Header Pitch 2,00mm	
Part No.:	T27B1079-
Customer:	

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	03.10.2018
APPD:	Schumi			FINISH	Jamy		Sheet No.	2 from 4	

EDCON-COMPONENTS



Ordering Informations


Serie	No. of Pos.	Construction	Contact Plating	Material	Special function	Pin Length Code	ROHS	Packing		
T27B1079-	XX	ST	G0	PB	N	A01	R	BU		

04 ~ 80Pos.	ST= Straight THT	G0= Gold Flash (Standard)	PB= P.B.T	N= No special	look Table No. 1	N= NO ROHS conform	BU= Bulk (Standard)
	T0= Tin plated	GA= 10µ Gold Plating	NY= Nylon-6T			R= ROHS conform	TU= Tube w/o Cap
	GB= 15µ Gold Plating	LC= LCP	P4= PA46			TC= Tube w. pic and Place Cap	
	GC= 20µ Gold Plating			TY= Tray packing w/o Cap			
	S0= Selectiv Plating Gold Flash / Tin					TR= Tape/Reel w. pic and Place Cap	


Female Header Pitch 2,00mm
Part No.: T27B1079-
Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	03.10.2018
APPD:	Schumi			FINISH	Jamy		Sheet No.		3 from 4


EDCON-COMPONENTS



Soldering Profile for Lead Soldering (P.B.T.)



Soldering Profile for Lead Free Soldering (Nylon 6T)



**Female Header Pitch
2,00mm**

Part No.: **T27B1079-**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	03.10.2018
APPD:	Schumi			FINISH	Jamy		Sheet No.	4 from 4	Customer:

www.edcon-components.com

email: info@edcon-components.com