



# EDCON-COMPONENTS





## Specifications

Current Rating:	1,0 Ampere
Insulator Resistance:	1000 Megaohm min.
Dielectric Withstanding:	AC 500V
Operating Temperature:	-.40°C to +105°C
Contact Material:	Copper, Alloy
Insulator Material:	P.B.T / PA6T
Standard:	PBT
Contact Plating:	Tin, Gold or Selective Plated
Standard:	Gold Flash Overall
Selectiv Plating:	Gold flash plated on contact area / tin plated on solder area
Max. Prozessing Temp.	look order Code Table

## Drawing ( dimensions all into mm)



## P.C.B Layout



PIN Header /Dual Row / Dual Body  
/ Pitch 1,27mm

Part No.: **T51C1116-**


DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	03.03.2023
APPD:	Schumi			FINISH	Jamy		Sheet No.		1 from 4

Customer:

[www.edcon-components.com](http://www.edcon-components.com)

email: [info@edcon-components.com](mailto:info@edcon-components.com)

# EDCON-COMPONENTS




## Pin Code length table free configuration

Order Code	Dimension (mm)			
	B	C	D	W
A01	1,65	8,51	0,00	5,80
A02	1,65	7,50	0,00	5,80
A03	1,65	6,50	0,00	5,80
A04	1,65	9,50	0,00	5,80
A05	1,65	10,00	0,00	5,80
A06	1,65	11,00	0,00	5,80
A07	1,65	12,00	0,00	5,80
A08	1,65	13,00	0,00	5,80
A09	1,65	14,00	0,00	5,80
A10	1,65	15,49	0,00	5,80
A11	3,85	6,00	0,00	5,80
A12	7,11	6,71	0,00	5,80
A13				
A14				
A15				
A16				
A17				
A18				
A19				
A20				
A21				
A22				

Order Code	Dimension (mm)			
	B	C	D	W
A23				
A24				
A25				
A26				
A27				
A28				
A29				
A30				
A31				
A32				
A33				
A34				
A35				
A36				
A37				
A38				
A39				
A40				
A41				
A42				
A43				
A44				

Order Code	Dimension (mm)			
	B	C	D	W
A45				
A46				
A47				
A48				
A49				
A50				
A51				
A52				
A53				
A54				
A55				
A56				
A57				
A58				
A59				
A60				
A61				
A62				
A63				
A64				
A65				
A66				




PIN Header /Dual Row / Dual Body  
/ Pitch 1,27mm

Part No.: **T51C1116-**

Customer:

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	03.03.2023
APPD:	Schumi			FINISH	Jamy		Sheet No.		2 from 4

# EDCON-COMPONENTS



## Ordering Informations

Serie	No. of Pos.	Construction	Contact Plating	Material	Special function	Pin Length Code	ROHS	Packing		
<b>T51C1116-</b>	<b>XX</b>	<b>SS</b>	<b>G0</b>	<b>PA</b>	<b>N</b>	<b>A01</b>	<b>R</b>	<b>BU</b>		


<b>XX</b> = total pin of header	<b>SS</b> = Straight SMT	<b>G0</b> = Gold Flash (Standard)	<b>PA</b> = Polyester 6T	<b>N</b> = Without Locating Peg	look table page 2	<b>N</b> =NO ROHS conform	<b>BU</b> = Bulk (Standard)	
		<b>T0</b> = Tin plated					<b>R</b> =ROHS conform	<b>TU</b> = Tube w/o Cap
		<b>GA</b> = 10µ Gold Plating						<b>TC</b> = Tube w. pic and Place Cap
		<b>GB</b> = 15µ Gold Plating						<b>TY</b> = Tray packing w/o Cap
		<b>GC</b> = 20µ Gold Plating						<b>TR</b> = Tape/Reel w. pic and Place Cap
		<b>S0</b> = Selectiv Plating Gold Flash / Tin						
		<b>TN</b> = Tin Plated						

PIN Header /Dual Row / Dual Body / Pitch 1,27mm	
Part No.:	<b>T51C1116-</b>
Customer:	

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	03.03.2023
APPD:	Schumi			FINISH	Jamy		Sheet No.		3 from 4


[www.edcon-components.com](http://www.edcon-components.com)

email: [info@edcon-components.com](mailto:info@edcon-components.com)



Soldering Profile for Lead Free Soldering

Classification Reflow Profile (JEDEC J-STD-020C)



PIN Header /Dual Row / Dual Body  
/ Pitch 1,27mm

Part No.: **T51C1116-**

DRW:	Jason	CHKD	Wilson	MATL:	Wilson	TOLERANCE	Mason	DATE	03.03.2023
APPD:	Schumi			FINISH	Jamy		Sheet No.	4 from 4	Customer: