



## R47003-010

### Features:

Size 1210
Lead Free and compliant with the European Union
Fast tripping resettable circuit protection
Surface mount packaging for automated assembly

### Technical Specifications:

- I<sub>H</sub>** Hold current maximum current device will pass without interruption in 25° C still air unless
- I<sub>T</sub>**: Trip current: minimum current that will switch the device from low resistance, Resistance in 25°C still unless otherwise specified.
- I<sub>max</sub>**. Maximum current device can VMAXIMAX 100 vcycles --- NO arcing or burning.
- V<sub>max</sub>**: Maximum Voltage device can withstand without damage at rated current.
- P<sub>d</sub>**: power dissipated from device when in the tripped state in 25°C still air unless otherwise specified.
- R<sub>min</sub>**: Minimum resistance of device as supplied at 25°C unless otherwise specified.
- R<sub>1</sub> max.** Maximum device resistance in the nonstripped state 1 hour post reflow.

### Approval:



<b>SMT POLY FUSE    SIZE</b>	
<b>1210</b>	
Part No.:	<b>R47003-010</b>
Customer:	


DRW:	Lexua	CHKD	Wilson	MATL:	ChuChu	DATE	06.04.2007
APPD:	Jimmy			FINISH	Josy	Sheet	1 from 3

Copyright by EDCON-COMPONENTS H.Schmitt 11.6.2009



## Technical Drawing and Informations

### Dimensions




A (mm)		B (mm)		C (mm)		D (mm)		E (mm)	
Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
3,00	3,43	2,35	2,80	0,50	0,85	0,25	0,75	0,076	--

### Performance Rating:

Range	ICH	IT	V max	I m ax	Pd typ	Maximum Time to Trip		Resistance:		
	(A)	(A)	(V DC)	(A)	(W)	Current (A)	Time (Sec.)	Rmin (Ω)	Rmax (Ω)	R1max (Ω)
	<b>100mA</b>	<b>0,100</b>	<b>0,25</b>	<b>30,0</b>	<b>10,0</b>	<b>0,6</b>	<b>0,50</b>	<b>1,00</b>	<b>2,10</b>	<b>9,00</b>

### PAD Layout



A (mm)	B (mm)	C (mm)
2,00	1,00	2,50

**SMT POLY FUSE SIZE 1210**

Part No.: **R47003-010**

Customer:


DRW:	Lexua	CHKD	Wilson	MATL:	ChuChu	DATE	06.04.2007
APPD:	Jimmy			FINISH	Josy	Sheet	2 from 3

Copyright by EDCON-COMPONENTS H.Schmitt 11.6.2009




### Soldering Information

#### Lead Solder Performance



#### Lead free Solder Performance



### Ordering Informations:

Item-No. & Range	ROHS	Packing
------------------	------	---------

<b>R47003-010</b>	<b>R</b>	<b>TR</b>
-------------------	----------	-----------

**010 = 100mA**

<b>R= ROHS</b>	<b>TR= Tape / Reel Standard)</b>
<b>N= Non ROHS</b>	
<b>BU= Bulk</b>	

**SMT POLY FUSE SIZE 1210**

Part No.: **R47003-010**

Customer:

DRW:	Lexua	CHKD	Wilson	MATL:	ChuChu	DATE	06.04.2007
APPD:	Jimmi			FINISH	Josi	Sheet	3 from 3

Copyright by EDCON-COMPONENTS H.Schmitt 11.6.2009