



R47005-300A

Features:

Size 2920
Lead Free and compliant with the European Union
Fast tripping resettable circuit protection
Surface mount packaging for automated assembly

Technical Specifications:

I_H Hold current maximum current device will pass without interruption in 25°C still air unless

I_T: Trip current: minimum current that will switch the device from low resistance, Resistance in 25°C still unless otherwise specified.

I_{max}. Maximum current device can VMAXIMAX 100 vcycles --- NO arcing or burning.

V_{max}: Maximum Voltage device can withstand without damage at rated current.

P_d: power dissipated from device when in the tripped state in 25°C still air unless otherwise specified .

R_{min}: Minimum resistance of device as supplied at 25°C unless otherwise specified.

R₁ max. Maximum device resistance in the nonstripped state 1 hour post reflow.

Approval:



SMT POLY FUSE	SIZE
2920	
Part No.:	R47005-300A
Customer:	


DRW:	Lexua	CHKD	Wilson	MATL:	ChuChu	DATE	26.11.2014
APPD:	Jimmy			FINISH	Josy	Sheet	1 from 3

Copyright by S.Tiede



Technical Drawing and Informations

Dimensions



A (mm)		C (mm)		B (mm)		D (mm)		E (mm)	
Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
7,40	8,00	5,05	5,45	0,500	1,20	1,20	1,80	0,550	--


Performance Rating:

Range	ICH	IT	V max	I m ax	Pd typ	Resistance:		
	(A)	(A)	(V DC)	(A)	(W)	Rmin (Ω)	Rtyp (Ω)	R1max (Ω)
3,00A	3,000	6,00	16,0	40,0	1,50	0,008	0,04	0,12

Information I should (A) (Temperatur Characteristics)

A	-20°C	0°C	25°C	30°C	40°C	50°C	60°C	70°C	85°C
3,00A	4,53	4,02	3,51	3,00	2,52	2,26	1,99	1,74	1,34

PAD Layout



A (mm)	B (mm)	C (mm)
4,60	2,00	5,30


SMT POLY FUSE	SIZE
	2920
Part No.:	R47005-300A
Customer:	

DRW:	Lexua	CHKD	Wilson	MATL:	ChuChu	DATE	26.11.2014
APPD:	Jimmy			FINISH	Josy	Sheet	2 from 3




Soldering Information

Lead Solder Performance



Lead free Solder Performance



Ordering Informations:

Item-No. & Range	ROHS	Packing
------------------	------	---------

R47005-300A	R	TR
--------------------	----------	-----------

300 = 3,00A

R= ROHS	TR= Tape / Reel Standard)
N= Non ROHS	
BU= Bulk	

SMT POLY FUSE	SIZE
2920	
Part No.:	R47005-300A
Customer:	

DRW:	Lexua	CHKD	Wilson	MATL:	ChuChu	DATE	26.11.2014
APPD:	Jimmi			FINISH	Josi	Sheet	3 from 3

Copyright by S.Tiede